

AJA FS1 Specifications



Specification	Value	Notes
SDI Input		
Standard	SMPTE 259M, 292M	
Connector	75 ohm BNC	
Return loss: 5Mhz to 1.5GHz	>18db	
Equalization (Belden 1694 cable): 270MHz	350m	
1.5GHz	140m	
SDI Output		
Standard	SMPTE 259M, 292M	
Connector	75 ohm BNC	
Return loss: 5Mhz to 1.5GHz	>18db	
Return loss: 1.5GHz to 3GHz	>18db	
Timing jitter: 270MHz	<0.1 UI	Genlock = freerun, Color Bars
1.5GHz	<0.5 UI	"
Alignment jitter: 270MHz	<0.1 UI	"
1.5GHz	<0.13 UI	"
Component Input		
Format	SMPTE, Betacam	
Connector	75 ohm BNC	
Return loss	>40 dB, 300 kHz to 6 MHz	
Quantization	12 bits	
Frequency response SD	Y: ±0.2 dB to 5 MHz	
	Pb/Pr: ±0.2 dB to 2 MHz	
Frequency response HD	Y: ±0.5 dB to 25 Mhz, -2.0 dB @ 30 Mhz	
	Pb/Pr: ±0.2 dB to 12.5 Mhz, -1.0 dB @ 15 Mhz	

Revised 5/19/09

AJA FS1 Specifications



Specification	Value	Notes
SNR	>65 dB	Flat field, gray
Component Output		
Format	SMPTE, Betacam, RGB	
Connector	75 ohm BNC	
Return loss	>40 dB 300 kHz to 6 MHz	
Quantization	12 bits	
Frequency response SD	Y: ± 0.2 dB to 5 MHz	
	Pb/Pr: ± 0.5 dB to 2.5 MHz	
Frequency response HD	Y: ± 0.25 dB to 25 Mhz, -3 dB @ 30 Mhz	
	Pb/Pr ± 0.25 to 12.5 Mhz, -3 dB @ 15 Mhz	
SNR	>65 dB	Flat field, gray
Composite/S Video Input		
Standard	NTSC, PAL	
Connector	75 ohm BNC, S Connector	
Return loss	>40 dB 300 kHz to 6 MHz	
Quantization	12 bits	
Frequency response	± 0.5 dB, to 5 MHz, Luminance	
SNR	65 dB	
Composite/S Video Output		
Standard	NTSC, PAL	
Connector	75 ohm BNC, S Connector	
Return loss	>40 dB 300 kHz to 6 MHz	
Quantization	12 bits	
Frequency response	± 0.1 dB to 6 MHz, Luminance	
DC offset	$< 0.0 \pm 50$ mV	
Differential gain	$< 0.5\%$	
Differential phase	$< 0.5^\circ$	
Transient response	$< 0.9\%$ K Factor	
SNR	>65 dB	

AJA FS1 Specifications



Specification	Value	Notes
Propagation Delay		
Video	1 frame nominal	
Audio	adjustable + 16 / -256ms with respect to video output	
Genlock Input		
Connector	75 ohm BNC	
Return loss	> 40 db, 300khz to 6 Mhz	
Signal type	NTSC/PAL analog composite, 300 mV Sync, ±300 mV Tri-level sync	
AES Input		
Standard	AES3, SMPTE276M	
Connector	75 ohm BNC	
Sensitivity	<200 mV	
Return loss	> 30 dB, 300khz to 6 Mhz	
Input audio rate	32 kHz to 96 kHz	Sample rate conversion
AES Output		
Standard	AES3, SMPTE276M	
Connector	75 ohm BNC	
Return loss	> 30 dB, 300khz to 6Mhz	
Jitter	< 0.7 ns	
Rise/fall time	2 ns (10% to 90%)	
Analog Audio Input		
Connector	Tascam 25 pin D	
Input impedance	30k ohms	
Input analog level	+12, +15, +18, +24db Full Scale Digital	
Frequency response	<±0.3 dB 20 Hz to 20 kHz	
THD	> -82 dB @ 1khz, -94 dB @ 20Khz	
SNR	> -94 dB @ +23 dBm	

AJA FS1 Specifications



Specification	Value	Notes
Analog Audio Output		
Connector	Tascam 25 pin D	
Output analog level	+12, +15, +18, +24db Full Scale Digital	
Frequency response	± 1 dB 20hz to 13khz, -3dB @ 20 Khz	
THD	>-85 dB	
SNR	>- 94 dB @ +23 dBm	
Weight and Dimension Measurements		
Height	1RU, 1.75 in. (4.5 cm)	
Width	19 in. (48.3 cm)	
Depth (including BNCs)	21.5 in. (54.6 cm)	