



# OG-FiDO-2R-12G

The OG-FiDO-2R-12G is a state of the art, openGear compatible, 2-channel Fiber to 12G-SDI converter, enabling 12G-SDI signals to be extended up to 10 km (32,808 ft) over standard single mode fiber optic cable. The two fiber inputs are completely independent allowing different 12G-SDI rates to be carried on each channel.

**\$1659 US MSRP**

AJA openGear OG-FiDO products are designed for use in high density openGear 2RU frames including AJA's OG-X-FR frame, with industry standard DashBoard software support on Windows®, macOS® and Linux®, offering remote control and monitoring over a PC or local network.

<https://www.aja.com/products/og-fido-2r-12g>

## Video Formats

- 270 Mbps - 12 Gbps, format agnostic

## Video Input Digital

- 2-channel independent 12G-SDI Single Mode LC Fiber connectors, SMPTE 297/259/292/424/2081/2082
- Nominal Wavelength: Rx 1260 nm (Min), 1620 nm (Max)
- Optical Sensitivity: -9 dBm (Max) for 12 Gbps, -10 dBm (Max) for 270 Mbps, 1.5 Gbps, 3 Gbps & 6 Gbps
- Overload Power: -2 dBm (Min)

## Video Output Digital

- 2-channel independent 12G-SDI BNC Outputs, SMPTE 259/292/424/2081/2082

## Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.967 Gbps, 2.970 Gbps, 5.934 Gbps, 5.940 Gbps, 11.868 Gbps, 11.880 Gbps - Auto Select
- All other rates are passed through and not reclocked

## User Interface

- openGear DashBoard network control software via Windows, macOS, or Linux

## Size

- openGear standard form factor, front slot and rear card
- Two slots required for each card

## Weight

- 0.5 lb (0.3 kg)

## Power

- openGear frame compatible, 3.0 watts max per card

## Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)