



# ROI-DVI

AJA's ROI-DVI Mini-Converter allows exceptionally high quality conversion of computer DVI and HDMI outputs to baseband video over SDI at an affordable price and a very portable size. With extensive audio functionality, incredible image scaling as well as aspect and frame rate conversion, ROI-DVI fulfills the growing need to properly incorporate computer signals into the video world without sacrificing budget or space.

**\$1245 US MSRP**

<https://www.aja.com/products/roi-dvi>

## Video Input Formats

- Computer Signals:
  - WUXGA (1920 x 1200) 60 Hz max
  - VGA (640 x 480) minimum
- Video Signals:
  - (HD) 1920 x 1080i 50, 59.94
  - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
  - (HD) 1280 x 720p 50, 59.94, 60
  - (SD) 625i, 525i
  - (SD) 580p, 480p

**Note:** Frame rates limited by the 166 mHz max pixel rate of the DVI receiver.

## Video Output Formats

- (HD) 1920 x 1080p 50, 59.94, 60, SMPTE 425-1 Level A mapping structure 1 (4:2:2 10-bit YCbCr)
- (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30
- (HD) 1920 x 1080i 50, 59.94, 60
- (HD) 1280 x 720p 50, 59.94, 60
- (SD) 625i 25
- (SD) 525i 29.97

## Color Range

- Full
- SMPTE

## Reference Source

- Free Run
- Ext Ref

## Reference Input

- Supported reference video inputs include:
  - 1080i tri-level sync
  - 1080p tri-level sync

- 720p tri-level sync
- 625i Color Black
- 525i Color Black
- 75 ohm terminating

## Video Input

- 1x DVI input connector (with embedded audio, up to 8-channels)

## Video Outputs

- DVI
  - 1x DVI loop through connector (with embedded audio, up to 8 channels)
- SDI
  - 3G-SDI, SMPTE-259/292/424, 1x BNC

## Audio Inputs

- 1x Analog 3.5mm TRS, 2-channel
- DVI embedded audio, 24-bit, 8-channel

## Audio Output

- SDI embedded audio, 24-bit, 2-channel or 8-channel

## User Interface

- USB port used with supplied cable and Mini-Config software application to configure device via Mac or Windows

## Size (w x d x h)

- 5.77" x 4.02" x 0.90" (146.56 x 102.11 x 22.86 mm)

## Weight

- 0.6 lb (0.3 kg)



## Power

---

- Uses AJA power supply model DWP-U-R1, included with purchase
- 100-240V, 50/60 Hz universal input
- +5 to 20V DC regulated, 8 watts max

## Environment

---

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)