

# Mini Config

## Release Notes – Version 2.3.0

### General

This release is recommended for all AJA MiniConfig software users. It adds support for a new Mini-Converter, the UDC.

### Supported Products

- Hi5-3D, Hi5-3G, HDP2 and UDC

### New Features

The new UDC module has the following features:

- Converts between SD, HD, and 3G HD formats
- Supports 1080p50/60
- SDI and HDMI output with 8 channel audio
- 2-channel RCA analog audio output
- Reference Input
- Configure via Dipswitch or USB port and supplied MiniConfig software
- Uses 5-20V power supply (sold separately)
- 5 year warranty

### Installing the Latest Software

The Mini-Converters come from the factory with a software CD and pre-installed with firmware. To ensure that you have the most current version of software/firmware available, please check the AJA website. To get the software, point your browser to:

<http://www.aja.com/support/converters/converters-mini-rackmount.php>

Current and past releases of the Mini Config software are available. Once there, the MiniConfig software files can be selected to download for configuring and upgrading your Mini-Converter module.

### Product User Manual

The manual provided with the Mini-Converter describes updating the software; please refer to it when updating software. The product manuals are located on the CD and installed with the software in the /AJA/MiniConfig/Documentation/ folder in your Start menu. The manual is also available online for download, here:

<http://www.aja.com/support/converters/converters-mini-rackmount-documents.php>

