

# AJA Mini-Config Release Notes - v2.21.2

## Control Software for AJA Mini-Converters

### General v2.21.2

---

This version of Mini-Config incorporates feature enhancements for the 12GM and Hi5-3D Mini-Converters.

Users of AJA Mini-Converters other than those listed above will not gain new functionality with this version of Mini-Config, however it is recommended to migrate to the most recent version even when using non-updated Mini-Converters.

### Improvements

---

#### 12GM

- Added Two Sample Interleave (2SI) to Square Division (Quadrant) pixel mapping.
- Added Square Division (Quadrant) to Two Sample Interleave (2SI) pixel mapping.
- Added a new analysis tool, (Input Timing tab), that displays any timing differences between SDI inputs.

#### Hi5-3D

- Added the ability to swap the Left and Right SDI inputs using AJA's Mini-Config application and/or the Hi5-3D physical dipswitch controls. Note that the functions for dipswitches 6, 7 and 8 have been modified to support this new feature.

### Installing the Latest Software

---

Mini-Converters come from the factory with the most current version of firmware pre-installed. To get the latest version of Mini-Config, visit the AJA website support area and select your Mini-Converter from the list:

<https://www.aja.com/category/mini-converters#support>

The Mini-Config software can be found in the Software section of the support page for your Mini-Converter. Previous releases of the AJA Mini-Config software are also available in the Software Archive section for each supported Mini-Converter.

## Firmware Upgrade Procedure

---

The manual provided with your AJA Mini-Converter describes the firmware update process; please refer to it in order to properly update your firmware. The product manuals are also installed with the software in the /AJA/Mini-Config/Documentation/ folder.

Individual product manuals are available online for download from the Mini-Converter section of the AJA website:

<http://www.aja.com/support>

## Products Supported In This Release

---

HD10MD4	Hi5-4K	HB-T-SDI
LUT-box	HA5-4K	HB-R-SDI
Hi5-3D	4K2HD	ROI
Hi5-3G	V2Digital	ROI-DVI
HDP2	V2Analog	ROI-HDMI
UDC	Hi5-Plus	ROI-DP
HDP3	HA5-Plus	ROI-SDI
OG-3G-AM	3G-AMA	Hi5-Fiber
HA5-Fiber	Hi5-4K-Plus	RovoRx-SDI
3G-AM	12GM	

# Technical Support

---

AJA Technical Support is free and available to help you answer questions or resolve issues with any of your AJA products.

To contact AJA Technical Support:

Email: [support@aja.com](mailto:support@aja.com)

Phone: +1-530-271-3190

Fax: +1-530-274-9442

Web: [www.aja.com/support](http://www.aja.com/support)

Shipping: 180 Litton Dr. Grass Valley, CA 95945 USA