




## OG-FIBER-2T-X

OG-FIBER-2T-X is no longer available. For more information about AJA fiber products please visit the Fiber Solutions page.

\$ US MSRP

<https://www.aja.com/index.php/products/og-fiber-2t-x>

### Video Formats

- 100 Mbps - 3 Gbps, format agnostic

### Video Input Digital

- 2-Channel independent 3G-SDI Inputs, SMPTE-259/292/424

### Video Output Digital

- 2-Channel independent CWDM LC Fiber Outputs, SMPTE-297\*
- Optical Power: -5dBm (min), 0dBm (max)
- Extinction Ratio: 7.5dB (Typ)

*\*Please see SFP Configurator for CWDM wavelength choices*

### Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.966 Gbps, 2.970 Gbps - Auto Select
- All other rates are passed through and not reclocked

### Size (w x d x h)

- openGear standard form factor, front slot and rear card
- Two slots required for each card

### Power

- openGear frame compatible, 2.5 watts max per card

### Environment

- Safe Operating Temperature: 0 to 40 degrees C (32 to 104 degrees F)
- Safe Storage Temperature (Power OFF): -40 to 60 degrees C (-40 to 140

degrees F)

- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)