

10 GigE IP Mini-Converters

SMPTE 2110 IP Video/Audio Receivers



Installation and Operation Guide

Version 2.0

Published February 19, 2019



Notices

Trademarks

AJA® and Because it matters.® are registered trademarks of AJA Video Systems, Inc. for use with most AJA products. AJA™ is a trademark of AJA Video Systems, Inc. for use with recorder, router, software and camera products. Because it matters.™ is a trademark of AJA Video Systems, Inc. for use with camera products.

CION®, Corvid Ultra®, Io®, Ki Pro®, KONA®, KUMO®, ROI® and T-Tap® are registered trademarks of AJA Video Systems, Inc.

AJA Control Room™, KiStor™, Science of the Beautiful™, TruScale™, TruZoom™, V2Analog™ and V2Digital™ are trademarks of AJA Video Systems, Inc.

All other trademarks are the property of their respective owners.

Copyright

Copyright © 2019 AJA Video Systems, Inc. All rights reserved. All information in this manual is subject to change without notice. No part of the document may be reproduced or transmitted in any form, or by any means, electronic or mechanical, including photocopying or recording, without the express written permission of AJA Video Systems, Inc.

Contacting AJA Support

When calling for support, have all information at hand prior to calling. To contact AJA for sales or support, use any of the following methods:

Telephone	+1.530.271.3190
FAX	+1.530.271.3140
Web	https://www.aja.com
Support Email	support@aja.com
Sales Email	sales@aja.com

Contents

Notices	2
Trademarks	2
Copyright	2
Contacting AJA Support	2
Chapter 1 – Introduction	5
Overview	5
Features	6
System Requirements	7
Simplified Block Diagram	7
I/O Connections	7
Control LAN, Ready, Link/Act, and Lock LED Behavior.	8
Installation Overview	8
Initial Installation for IP Mini-Converters	9
REST API Documentation	10
Chapter 2 – eMini-Setup	11
Overview	11
Acquiring eMini-Setup	11
eMini-Setup Documentation	11
Installing eMini-Setup	12
PC Installation	12
Mac Installation	13
Running eMini-Setup	13
PC Startup	14
Mac Startup	14
Operating eMini-Setup	14
Control LAN Tab Screen	15
Media Network 1 Tab Screen	16
Media Network 2 Tab Screen	17
Update Tab Screen.	18
Firmware Update Procedure.	18
Info Tab Screen	19
Chapter 3 – 10 GigE IP Mini-Converters Web Interface.	20
Overview	20
Remote Control Overview	20
Networking Option – Using Only the Media LAN Port for Control and Media Settings	20
Web Browser via Ethernet	21
General Screen Information	21
Status Screen	23
Config Screen	24
Presets Screen	29
Presets Screen Controls	29
Network Screen	30
Firmware Screen	32
Downloading and Installing Updated Firmware	33
Booting the 10 GigE IP Mini-Converters from the Safeboot Firmware	33
Appendix A – Frequently Asked Questions.	35
Appendix B – Specifications	37
IPR-10G2-HDMI Tech Specs	37
IPR-10G2-SDI Tech Specs.	38

Appendix C – Safety and Compliance	40
Warranty and Liability Information	48
Limited Warranty on Hardware.	48
Limitation of Liability	49
Governing Law and Language; Your Rights.	49
Index.	50

Chapter 1 – Introduction



Overview

AJA 10 GigE IP Mini-Converters are designed for point of use applications for reception and decoding of IP based video sources. Rugged, compact and fanless, the 10 GigE IP Mini-Converters provide the bridge between Baseband and IP video for a range of applications, such as receiving video over IP from remote facilities in post production, source monitoring, digital signage, and video walls. 10 GigE IP Mini-Converters ease the cost of extensive monitoring distribution in a facility.

The 10 GigE IP Mini-Converters decode SMPTE 2110 and formats the data for either HDMI or SDI output. The audio associated with the video stream is extracted, synchronized, and then embedded into the HDMI or SDI signal as well as output on a stereo analog RCA audio output.

Features

IPR-10G2-HDMI

- SMPTE 2110 audio, video receiver
- Rugged, fanless design
- 2x 10 GigE SFP+ cages for media LAN (providing support for hitless switching) with status light
- 1x 1 GigE RJ45 socket for control LAN with status light
- Dedicated HDMI receiver with full size HDMI 1.4b video port
- Support for HD up to 1080 60p, YCbCr 4:2:2
- Full 10-bit pixel processing pipeline
- Embedded HDMI audio output (up to eight channels)
- 2x RCA analog audio output
- 1x BNC Reference In

NOTE: Reserved for future potential features

- 1x mini-USB port for initial network configuration with AJA eMini-Setup software
- Complete control interface on any web browser from a built-in web server
- Customizable control with AJA REST API
- 5-year international warranty and support

IPR-10G2-SDI

- SMPTE ST 2110 audio, video receiver
- Rugged, fanless design
- 2x 10 GigESFP+ cages for media LAN (providing support for "hitless switching) with status light
- 1x 1 GigERJ45 socket for control LAN (with status light)
- 2x 3G-SDI Output
- Support for HD up to 1080 60p, YCbCr4:2:2
- Full 10-bit pixel processing pipeline
- Embedded SDI audio output (up to eight channels)
- 2x RCA analog audio output
- 1x BNC Reference In

NOTE: Reserved for future potential features

- 1x mini-USB port for initial network configuration with AJA eMini-Setup software
- Complete control interface on any web browser from a built-in web server
- Customizable control with AJA REST API
- 5-year international warranty and support

Software

- Built in web server for full remote control and configuration
- eMini-Setup software with a USB connection for initial configuration


System Requirements

Remote computer configuration and control is accomplished using the 10 GigE IP Mini-Converters' internal web server. A macOS X or Windows computer with a web browser installed is all that is required. Additionally, initial configuration using eMini-Setup will require a USB port between the host computer and the 10 GigE IP Mini-Converter.

NOTE: Safari is the preferred web browser for control on the Mac, and additionally Chrome and Firefox on Windows. Other web browsers may work, but AJA cannot guarantee consistent operation for all web browsers or web browser versions.

Simplified Block Diagram

Figure 1. 10 GigE IP Mini-Converters Simplified Block Diagram



I/O Connections

Figure 2. IPR-10G2-HDMI Connections



Figure 3. IPR-10G2-SDI Connections



Control LAN, Ready, Link/Act, and Lock LED Behavior

The Control LAN LED illuminates to indicate a link. Blinking indicates activity.

The Ready LED illuminates green when the unit has finished powering up and is ready to use.

The Link/Act LED 1 and Link/Act LED 2 behavior is as follows:

- Off - No SFP+ module present
- Red - SFP+ module present, no link
- Green - Link is up
- Green flash - Link is up and there is Tx or Rx activity

The Lock LED behavior is as follows:

- Off - No Precision Time Protocol (PTP) is detected
- Red - A PTP error is detected
- Yellow and flashing - Locking Phase 1
- Yellow - Locking Phase 2
- Green and flashing - Locking Phase 3
- Green - Signal is locked

NOTE: Achieving locked status may take 5 or more minutes depending on network jitter behavior. The output of the unit will still function during the locking period.

Installation Overview

Detailed instructions are provided in ["Chapter 2 – eMini-Setup" on page 11](#) and ["Chapter 3 – 10 GigE IP Mini-Converters Web Interface" on page 20](#). As an overview, however, 10 GigE IP Mini-Converters installation typically consists of the following steps:

1. Apply power to the unit.
2. Use eMini-Setup and a USB connection to determine the unit's IP address (DHCP by default), or to initially configure the unit's network settings. Following this initial configuration, you will be able access the unit's user interface through a web browser instead.

3. Close the eMini-Setup application, and disconnect the USB cable.
4. Connect the unit to your Ethernet network. Use the Control LAN to make configuration changes. Use Media LAN 1 and Media LAN 2 for the incoming video over IP stream.
5. Launch a web browser and access the 10 GigE IP Mini-Converter using its IP address. Continue device configuration as needed from the web interface.
6. Connect the 10 GigE IP Mini-Converter's output.
7. Configure the 10 GigE IP Mini-Converter's basic operation.

The current 10 GigE IP Mini-Converter's configuration settings are retained even when powered off, so subsequent installations for an identical decoding or encoding session can be done with the following simple steps:

1. Apply power to the 10 GigE IP Mini-Converter.
2. Connect the unit to your network using the Control LAN, Media LAN 1 and Media LAN 2 and connect the unit's output.

NOTE: Three LAN connections to the unit are not necessarily required on an ongoing basis. If it is desirable for your installation, after the 10 GigE IP Mini-Converter is set up, you can access all control parameters through one of the Media LANs with the appropriate network configuration. See ["Networking Option – Using Only the Media LAN Port for Control and Media Settings"](#) on page 20 for more information.

NOTE: The 10 GigE IP Mini-Converters pack an unprecedented feature set into the mini converter box. As a result, the unit uses approximately 13 watts of power. It will be very warm to the touch, which is normal. The unit is engineered to operate across the full temperature range, from 0 to 40 degrees C.

NOTE: For highest reliability, the mini converters rely on convection cooling instead of using a built-in fan. Therefore, when installing the units, mount in a location where they have access to air for proper cooling. Do not stack the 10 GigE IP Mini-Converters with other mini converters or other powered equipment.

Initial Installation for IP Mini-Converters

Network Configuration

The 10 GigE IP Mini-Converter requires a network connection to decode an IP stream. 10 GigE IP Mini-Converters are shipped from the factory with DHCP enabled, so if your network has a DHCP server, by simply connecting the 10 GigE IP Mini-Converter to your network with an Ethernet cable, the DHCP server will assign the unit a compatible IP address.

10 GigE IP Mini-Converters are shipped from the factory with UPnP (Universal Plug and Play) services enabled, so they are discoverable through Windows Explorer (for networked Windows PCs).

The eMini-Setup application, available as a free download from the AJA website, is used to identify the 10 GigE IP Mini-Converter's current IP addresses, if configured, or to manually set the initial network configuration to work in your environment. Refer below to ["Chapter 2 – eMini-Setup"](#) on page 11 for information about installing and using AJA's eMini-Setup application.

Once configured and connected to your network, the 10 GigE IP Mini-Converter is ready for decoding.

REST API Documentation

AJA's REST automation API provides a platform from which you can issue commands to an AJA device's internal web server, allowing remote systems the ability to control AJA embedded or networked devices. With this control framework, you can build integration and automation scripts, using any scripting language, allowing you to take full advantage of the device's functionality.

This documentation is available at the following link:

https://gitlab.aja.com/pub/rest_api

Chapter 2 – eMini-Setup

Overview

This chapter describes using the eMini-Setup application to initially communicate with and configure a 10 GigE IP Mini-Converter over a direct USB connection. Once configured, the IP Mini-Converter can be accessed via an Ethernet network using a web browser. Subsequently, that device can then be reconfigured over that network, using its IP address and built-in web server.

NOTE: *The eMini-Setup application is only used to setup selected Ethernet capable AJA devices, and cannot be used to connect to or setup other AJA Mini-Converters.*

The general procedure is:

1. Acquire eMini-Setup from the AJA website and install the eMini-Setup application onto a computer.
2. Connect the IP Mini-Converter to that computer's USB port.
3. Launch the eMini-Setup application.
4. Go to the Control Network tab and Media Network tabs, where the IP address settings are displayed. You can use the existing DHCP assigned IP address, or it can be changed manually.
5. You can also use eMini-Setup to load firmware to the device, although this can also be done quickly and easily using the web browser interface.

Acquiring eMini-Setup

AJA's eMini-Setup application is available for download from the AJA website.

To download the latest eMini-Setup package, which includes the eMini-Setup application and documentation:

1. Go to:
<https://www.aja.com/family/software#eminisetup>
2. Click the link corresponding to the version you want to download for Mac or Windows.

NOTE: *eMini Setup version 2.0 is the first version to support IPR-10G2-HDMI and IPR-10G2-SDI. Earlier versions will not work with these specific products.*

eMini-Setup Documentation

Included with the eMini-Setup download is the AJA device's *Installation and Operation Guide*, which can be accessed from the eMini-Setup UI via the Help/Manual drop-down menu. This manual includes eMini-Setup information.

Documentation can also be accessed directly from the Mac eMini-Setup installer in the Documentation folder.

Documentation included with the eMini-Setup application is the version available at the time of distribution. However, AJA's documentation can be updated regularly, so newer versions may exist.

To download just the latest documentation, go to:

Click the support button and open the Manuals link.


Installing eMini-Setup

PC Installation

To install eMini-Setup on a Windows PC:

1. Download the application from the AJA website. See "[Acquiring eMini-Setup](#)" on page 11.
2. Open the AJA_eMini-Setup_win.zip file.
3. Double-click on the AJA_eMini-Setup.msi file.
4. The Setup Wizard will guide you through the installation.


Figure 4. eMini-Setup PC Wizard



5. Click Next to begin. Answer the questions in the subsequent dialogues, including device software installation if displayed. When finished, an AJA eMini-Setup shortcut will be installed on the desktop, and you will be able to locate the eMini-Setup application in the AJA folder in the Programs listing.

NOTE: *If the eMini-Setup application already exists on the PC, a different Setup Wizard appears.*

Figure 5. eMini-Setup Wizard, Re-installation



With this screen you can **Repair** (reinstall) or **Remove** (uninstall) eMini-Setup on the PC.


Mac Installation

To install the application on a Mac:

NOTE: Mac computers must be Intel-based (G5, G4 and earlier models will not work with eMini-Setup).

1. Download the application from the AJA website. See ["Acquiring eMini-Setup" on page 11](#).
2. Unzip the file.
3. Double-click on the AJA eMini-Setup.dmg file.
4. Answer the prompt and a utility program will be launched.

Figure 6. eMini-Setup Mac Installer



5. To complete the installation drag the "AJA eMini-Setup" icon to the Applications folder.


Running eMini-Setup

Connect your Ethernet capable AJA device to the PC or Mac via the supplied USB cable, and then connect the external power supply (supplied) to that AJA device.

PC Startup

To run eMini-Setup on a PC, double-click on the AJA eMini-Setup icon on your desktop, or open the AJA folder in the program list and click on the AJA eMini-Setup application located inside the eMini-Setup folder.

Figure 7. Launching eMini-Setup on a PC




Mac Startup

To run eMini-Setup on a Mac, open the Applications folder and locate the AJA eMini-Setup application. Double-click the application to launch it.

Operating eMini-Setup

The eMini-Setup application provides a graphical user interface for viewing settings, modifying settings, and updating software.

Figure 8. Example eMini-Setup Screen



Selecting an AJA device from the pull down menu on the upper right causes eMini-Setup to connect to the selected AJA device.

Version - The version of firmware installed in the AJA device is displayed below the graphic.

Sn - This is the factory set unique serial number of your AJA device. If you ever call AJA Support for service, you may be asked for this number.

A status field at the bottom of the screen shows if the eMini-Setup application is connected and communicating with an AJA device.


File Menu - The File drop-down menu on the eMini-Setup application bar has a Revert to Factory Settings menu item that allows you to change the settings back to the AJA device's factory defaults.

Edit Menu - The Edit drop-down menu has standard Cut, Copy and Paste functions for editing text.

Help Menu - The Help drop-down menu has a link to the AJA device's manual.

Control LAN Tab Screen

Figure 9. eMini-Setup Control LAN Tab Screen



Use this Control LAN tab to change the network setup on the connected AJA device. You must click the Apply button to initiate any network configuration changes.

IP Address Type - Choose from DHCP (default) or Static IP Address.

NOTE: A basic setup would be to run an Ethernet cable directly between the device and your laptop and set both the computer and IPR to sequential static IP addresses. This provides a rapid way to set up to access the web user interface.

IP Address - The current IP Address is displayed. A different IP address can be entered.

Subnet Mask - The current Subnet Mask is displayed. A different subnet mask can be entered.

Gateway - The current Gateway address is displayed. A different gateway address can be entered.


UPnP Host - Choose from Enable or Disable to control whether the AJA device makes itself visible for Windows network browsing.

MAC Address - This is the permanent MAC address of the Control LAN Ethernet port of the AJA device.

Open Web Page - Opens the IP Mini-Converter's web interface in a web browser.

Media Network 1 Tab Screen

Figure 10. eMini-Setup Media LAN 1 Tab Screen



Use this Media LAN 1 tab to change the corresponding media network setup on the connected AJA device. You must click the Apply button to initiate any network configuration changes.

IP Address Type - Choose from DHCP or Static IP Address.

NOTE: If you intend to directly connect an IPT to an IPR, then you will need to use sequential static IP addresses for both units (Transmit and Receive).

IP Address - The current IP Address is displayed. A different IP address can be entered.

Subnet Mask - The current Subnet Mask is displayed. A different subnet mask can be entered.


Gateway - The current Gateway address is displayed. A different gateway address can be entered. On the Media LAN, the gateway may be left blank. (A gateway is required on the Control LAN).

MAC Address - This is the permanent MAC address of the Media LAN Ethernet port of the AJA device.

Open Web Page - Opens the IP Mini-Converter's web interface in a web browser.

Media Network 2 Tab Screen

Figure 11. eMini-Setup Media LAN 2 Tab Screen



Use this Media LAN 2 tab to change the corresponding media network setup on the connected AJA device. You must click the Apply button to initiate any network configuration changes.

IP Address Type - Choose from DHCP or Static IP Address.

NOTE: If you intend to directly connect an IPT to an IPR, then you will need to use sequential static IP addresses for both units (Transmit and Receive).

IP Address - The current IP Address is displayed. A different IP address can be entered.

Subnet Mask - The current Subnet Mask is displayed. A different subnet mask can be entered.


Gateway - The current Gateway address is displayed. A different gateway address can be entered. On the Media LAN, the gateway may be left blank. (A gateway is required on the Control LAN).

MAC Address - This is the permanent MAC address of the Media LAN Ethernet port of the AJA device.

Open Web Page - Opens the IP Mini-Converter's web interface in a web browser.

Update Tab Screen

Figure 12. eMini-Setup Update Tab Screen



Use this Update tab to install new firmware.

Installed - This field shows the version of the firmware currently installed.

Browse - This button opens a navigation window, allowing you to select the firmware and load that version of firmware into the AJA device's non-volatile memory.

Progress - This indicator bar shows the progress of firmware installation.


Firmware Update Procedure

1. Check the AJA website for new firmware.
2. If new software is found, download it and uncompress the file archive (.zip).
3. Connect the device to a Mac or PC via a USB port on the computer.
4. Click the Update tab. Click the Browse button. Navigate to the firmware (.ajas extension), open it, and confirm the update. Progress will be shown via the "Progress" bar.
5. After the update, the AJA device must be rebooted by clicking on the Reboot button in the prompt window.

See also: "[Firmware Screen](#)" on [page 32](#) regarding the process of working with firmware with the IP Mini-Converter's Web UI.

Info Tab Screen

Figure 13. eMini-Setup Info Tab Screen



This tab provides basic information about the connected AJA device. This information is mostly useful when calling AJA Support for service or technical support.

System Name - This field allows you to give your AJA device a unique name. This can be useful if you have several attached to a Mac/PC via USB so you can distinguish between them easily.

Type - This is the factory set model name of the AJA device.

Authentication - If Authentication has been Enabled on the web browser Access tab, you can disable the security feature by clicking the Disable button.

Chapter 3 – 10 GigE IP Mini-Converters Web Interface

Overview

Once you have established network connectivity with the 10 GigE IP Mini-Converter, you can further configure and more fully control the unit through its web interface. Subsequently, eMini-Setup is no longer required to interface with the unit.

NOTE: It is often best to remove the USB connection once you have acquired the web interface. This prevents accidentally using eMini-Setup to change parameters already set via the web UI.

Remote Control Overview

An optimized web server in the 10 GigE IP Mini-Converter allows remote control and parameter setting adjustments via a browser client running on a network wired computer. The network can be a closed local area network, a direct connection between a 10 GigE IP Mini-Converter and a computer, or even exposed through a firewall to a WAN.

Each 10 GigE IP Mini-Converter uses a standard RJ-45 connector for the Control LAN connection, and two SFP+ cages for the 10 Gbps Ethernet Media LAN connections.

NOTE: Safari is the preferred web browser for control on the Mac, and additionally Chrome and Firefox on Windows. Other web browsers may work, but AJA cannot guarantee consistent operation for all web browsers or web browser versions.

To connect to the 10 GigE IP Mini-Converter, attach the unit to your network and enter its Control Network IP address into the web browser. If authentication has been configured, you may need to enter a password.

Networking Option – Using Only the Media LAN Port for Control and Media Settings

To reduce facility cabling to the 10 GigE IP Mini Converter, it is an option to setup your network connection through an Ethernet switch via the Media LAN ports (rather than using the dedicated Control Port). This means that you will have just one or two cables to the unit, instead of two or three.

To implement this approach, follow these general steps:

1. Note the IP address of the unit's Media LAN 1 or Media LAN 2 port. This should be a static IP address.
2. Connect the controlling computer's Ethernet port that is being used to control the unit into an Ethernet switch. This requires disconnecting the Ethernet cable from the Control LAN port of the unit.
3. Connect the Media LAN port of the unit into the Ethernet switch.
4. Connect the source of the Media IP stream into the Ethernet switch.
5. Set the controlling computer's Ethernet port that is being used to control the 10 GigE IP Mini-Converter to DHCP.

6. From the controlling computer, point a web browser to the IP address noted in step 1. The 10 GigE IP Mini-Converter's web user interface displays in the browser.

Web Browser via Ethernet

General Screen Information

All IP Mini-Converter web screens have certain areas and controls in common. Vertical and horizontal scroll bars appear when information extends past the border of a panel.

The round blue Up/Down arrow button on each panel and many status parameters opens and closes that pane or set of parameters.

Menu Panel

On the left of each screen is a Menu panel listing all the available screens. Click any of these links to jump to that screen.

Alarms Panel

Alarms are displayed in a panel on the left side of each screen. Clicking on the arrow opens or closes this panel to show or hide the alarms. Hovering the mouse over an alarm (red) or warning (yellow) may provide additional detail about the condition.

Connections Panel

On the right side of every screen is a Connection panel listing information for the connected IP Mini-Converter.


Network Panel

Also on the right is a Network pane that lists other IP Mini-Converters on the network. The gear icon opens the Network Screen, the same as selecting Network from the Menu Panel. Right-clicking on the name of an IP Mini-Converter in this list allows you to turn on the Identify feature, which will blink all four of the Ethernet LEDs of that device at a 1 second rate.

Parameters and Information

The rest of the screen displays all the parameter selections and information available for the selected IP Mini-Converter screen.

Figure 14. Overview of Web Browser User Interface




Dynamic Controls

- Hovering the mouse on a parameter name displays a brief description of its function.
- From the Config Screen, right clicking on the parameter name resets just that parameter to its factory default.
- For values with sliders, fine control is achieved using the arrow keys on the keyboard to move the slider the minimum amount. The numeric value can also be clicked on to enter a specific value.

Status Screen

Figure 15. 10 GigE IP Mini-Converters Status Screen



The Status screen reports the current status and settings for:

- Input Status
- Video Output Clock Status
- Network Status
- Firmware Status

Each group of parameters can be expanded or collapsed.

Config Screen

Figure 16. IPR-10G2-HDMI Config Screen 1 of 3

The screenshot displays the IPR-10G2-HDMI configuration interface. The top bar shows the title 'IPR-10G2-HDMI' and the AJA VIDEO SYSTEMS logo. The left sidebar contains a 'Menu' with options: Status, Config (highlighted), Presets, Network, and Firmware. Below the menu is an 'Alarms' section with a 'None' button. The main area is titled 'IPR-10G2-ENG003' and 'Config Page'. It lists various configuration parameters with their current values and dropdown menus for selection. The right sidebar shows 'Connection' details (Serial Number, Software Version, Connection Status) and a 'Network' list of connected devices.

Parameter	Value
System Name	IPR-10G2-ENG003
User Authentication	Disabled
Identify LED	Off
UPnP Host	Enable
IGMP Version	v3
Video Output Clock Selection	PTP
PTP Domain	0
PTP Preferred Grandmaster ID	-none-
PTP Grand Master Capable	Disable
Hitless Media Support	Enable
Hitless Window Size(ms)	1

The Config Screen, shown in three parts, has the parameters required for the general operation of the IPR-10G2 Mini-Converters.

System Name

Defines a name for the system and gives it a unique identifier. This name is used when displaying systems through the web interface.

User Authentication

Enable or disable user password authentication for the web interface.

Identify LED

Enables flashing of the Ethernet LEDs on the unit.

UPnP Host

Enable or disable network discovery using Universal Plug and Play.

IGMP Version

Select the Internet Group Management Protocol Version. AJA supports IGMP v2 and v3.

NOTE: It is important to know which version of IGMP is in use on your network. Selecting the wrong IGMP version may cause long delays in processing multicast subscriptions. See your network engineer for more information.

Video Output Clock Selection

Select which clock source you want to use for the video output.

PTP - Use the current Precision Time Protocol (PTP) master on the network.

Lock to Input - Use the input signal as the clock source.

PTP Domain

NOTE: *Applicable only if PTP is selected for Video Output Clock Selection.*

While it is possible that there could be multiple PTP domains, most implementations will use "0". If unsure, consult with your network administrator. Possible values range from 0 to 127.

PTP Preferred Grandmaster ID

NOTE: *Applicable only if PTP is selected for Video Output Clock Selection.*

There can be multiple Grandmaster IDs. However, most of the time, it will be automatically determined. Typically, it is the same as the Ethernet address for the port of the Grandmaster.

Example of a PTP Grandmaster ID:

- 08-00-11-FF-FE-22-04-D6

PTP Grand Master Capable

NOTE: *Applicable only if PTP is selected for Video Output Clock Selection.*

For local demonstration purposes only, the IPR-10G2-HDMI and IPR-10G2-SDI can act as a grandmaster in network environments where there is not one already present, such as during basic testing, setting up a PoC or demonstration.

WARNING: *Do not enable this control unless you have first checked with your network administrator.*

Disable - Disables the PTP Grand Master capability.

Enable - Enables the PTP Grand Master capability.

Hitless Media Support

When enabled, the unit will accept signals from both Media LAN 1 and Media LAN 2, allowing for hitless media switching if one of the signals is interrupted. When disabled, the unit will take a signal only from Media LAN 1.

Disable - Disables hitless media support.

Enable - Enables hitless media support.

Hitless Window Size (ms)

NOTE: *Applicable only if Hitless Media Support is enabled.*

Set the amount of time in milliseconds that the unit will look for redundant packets to decide to accept or reject them for hitless media switching.

To determine the hitless window size, consider any delay between the signals, expected jitter, along with any other sources of potential delay between signals.

Possible values range from 1 to 50. The actual range is determined by the signal's frame rate, raster size and other factors.

Figure 17. IPR-10G2-HDMI Config Screen 2 of 3

Input Stream Selection

Select SDP, Manual or NMOS/Ember.

SDP - The SDP method greatly simplifies the configuration process for the Input Stream Selection fields. Selecting SDP causes the following four fields to display:

- **SDP URL Video** - Enter the SDP URL Video string. For example:
http://172.16.0.109/txch2v.sdp
- **SDP URL Audio** - Enter the SDP URL Audio string. For example:
http://172.16.0.109/txch2a1.sdp
- **SDP URL Video 2** - Enter the SDP URL Video string. For example:
http://172.16.0.109/txch2v.sdp
- **SDP URL Audio 2** - Enter the SDP URL Audio string. For example:
http://172.16.0.109/txch2a1.sdp

The strings entered into the **SDP URL Video** and **SDP URL Audio** fields point to SDP files that are created by the source that is transmitting the video signal.

The SDP files contain all required configuration parameters for the following **Input Stream Selection** fields:

- Video Input Format
- Audio Channels
- Audio Packet Interval
- Video Destination Address
- Video Source Address
- Audio Destination Address
- Audio Source Address.
- Video 2 Destination Address
- Video 2 Source Address

- Audio 2 Destination Address
- Audio 2 Source Address

Manual - When Manual is selected, you must enter configuration parameters manually into the following **Input Stream Selection** fields:

- Video Input Format
- Audio Channels
- Audio Packet Interval
- Video Destination Address
- Video Source Address
- Audio Destination Address
- Audio Source Address
- Video 2 Destination Address
- Video 2 Source Address
- Audio 2 Destination Address
- Audio 2 Source Address

NMOS/Ember - When NMOS/Ember is selected, the unit announces its presence to the network and the controller registers that it is there and what its capabilities are. Input stream selection occurs through network discovery and communication with facility automation.

Figure 18. IPR-10G2-HDMI Config Screen 3 of 3

Video Signal Generator

You can output a test video signal to validate video signal connections. Select Off or Test Pattern.

Off - No video signal is generated.

Test Pattern - Color bars with a moving gray line are generated in the currently selected video format and sent to the Video Output.

NOTE: The Test Pattern is supported only in 1080p and 1080i formats.

Audio Signal Generator

You can output a test audio signal to validate audio signal connections. Select Off or 400 Hz Tone.

Off - No audio signal is generated.

400 Hz Tone - A 400 Hz tone is generated on both channels of a pair and sent to the analog RCA audio outputs. Each channel pair is at a different volume. Channel pair 1/2 is the loudest. Channel pair 7/8 is the softest.

Audio Delay

Use the Audio Delay control as needed to synchronize audio and video signals.

0 to 100 Milliseconds - Use the slider control with a mouse or the right and left arrow keys on your keyboard to adjust the audio delay setting.

HDMI Audio Mode

Determine how you want the HDMI audio to function. It can auto-detect which channels are carrying the audio (either Channels 1-2 or Channels 1-8), or you can manually select which channels will carry audio. Select one of the following:

- Auto
- Channels 1-2
- Channels 1-8

Analog Audio Channels

Select which pair of analog audio channels you want to go out through the analog RCA audio outputs. Choose one of the following:

- Channels 1 & 2
- Channels 3 & 4
- Channels 5 & 6
- Channels 7 & 8

NMOS Enable


Enable or disable network discovery for the device.

Ember+ Enable

Enable or disable network discovery for the device.

Presets Screen

Figure 19. IPR-10G2-HDMI Presets Screen



The Presets screen allows you to save Preset Configurations into 20 separate memory registers and recall the presets whenever needed.

The Presets screen also includes Export and Import functions that allow exporting one or all presets to your computer as files and importing exported preset files from your computer. A displayed message indicates successful or failed saves, recalls, exports, and imports.

Presets Screen Controls

Factory Reset - Factory Reset recalls all editable parameters to their factory default settings. Individual presets and Network settings, such as the IP Addresses, are not affected.

Recall - The Recall buttons recall the saved preset configurations.

CAUTION: When you recall a Preset Configuration, the recalled preset immediately replaces the system's existing configuration. All previous settings are lost unless you have previously stored them in another preset configuration or an exported file.

Save - The Save buttons let you save the current configuration into the preset register with the associated name and number. A preset is a set of all parameters as they were set at the time the preset was saved. Only editable parameters are saved in the presets. Non-editable parameters are not saved.

To change a preset name, click in the name's text field, type a new name, and press Enter to save the name. After entering text, you can click the mouse outside of the edit box to exit without changing the name.

CAUTION: IP Mini-Converter stored presets may contain a web server access password. If you share an exported preset to someone, that person can extract the password. Before loaning the device to someone, or returning it as a rental, it is recommended that you clear the device of sensitive information.

Export - The Export buttons save the associated preset contents to a file on your computer. The file gets exported to the default download location specified in your browser options. The file name is the same as the preset name with the suffix *.presets*. If you export multiple files for the same preset, a number gets appended to ensure a unique file name. The file size is small, usually less than 100 kilobytes.

Import - The Import buttons let you browse for and import a preset file on your computer into the preset register associated with the selected button. A dialog box warns you that the operation will overwrite the current preset contents with the file contents. You can only import presets from an IP Mini-Converter.

Erase - The Erase buttons erase the data in that preset.

Export Presets 1–20 (All) - Export All lets you save the contents of all presets to a file on your computer.

The file gets exported to the default download location specified in your browser options with the name *all.presets*. If you export multiple files, a number gets appended to ensure a unique file name.

Import Presets 1–20 (All) - Import All lets you browse for and import a previously exported *all.presets* file from your computer. A dialog box warns you that the operation will overwrite all 20 current preset contents with the contents stored in the file.

Erase Presets 1–20 (All) - Erase All erases all data from all the presets. A dialog box warns you that the operation will erase all 20 current presets.

Network Screen

Use the Network Configuration Control Tab to configure or modify settings for the Control LAN Ethernet port.

Figure 20. IPR-10G2-HDMI Network Configuration Control Tab

The screenshot shows a web-based configuration interface titled "Network Configuration". It has three tabs: "Control", "Media1", and "Media2". The "Control" tab is selected. Under the "IP Address Type" section, "Static" is chosen. Below this, there are input fields for "IP Address" (10.3.188.113), "Netmask" (255.255.0.0), and "Default Gateway" (10.3.0.3), followed by an "Apply" button. The "MAC Address" is displayed as 00:0C:17:88:1D:0C, and the "Link State" is 1000MBit Full-Duplex.

Use the Network Configuration Media 1 Tab to configure or modify settings for the Media 1 SFP+ cage for 10 Gbps Ethernet port.

Figure 21. IPR-10G2-HDMI Network Configuration Media 1 Tab

The screenshot shows the 'Network Configuration' window with the 'Media1' tab selected. The 'IP Address Type' is set to 'DHCP'. Below this, the 'IP Address' is 172.16.250.7, 'Netmask' is 255.255.0.0, and 'Default Gateway' is 0.0.0.0. The 'MAC Address' is 00:0C:17:88:1D:0D and the 'Link State' is 10000MBit Full-Duplex.

Network Configuration	
Control Media1 Media2	
IP Address Type DHCP	
IP Address	172.16.250.7
Netmask	255.255.0.0
Default Gateway	0.0.0.0
MAC Address	00:0C:17:88:1D:0D
Link State	10000MBit Full-Duplex

Use the Network Configuration Media 2 Tab to configure or modify settings for the Media 2 SFP+ cage for 10 Gbps Ethernet port.

Figure 22. IPR-10G2-HDMI Network Configuration Media 2 Tab

The screenshot shows the 'Network Configuration' window with the 'Media2' tab selected. The 'IP Address Type' is set to 'DHCP'. Below this, the 'IP Address' is 172.16.250.3, 'Netmask' is 255.255.0.0, and 'Default Gateway' is 0.0.0.0. The 'MAC Address' is 00:0C:17:88:1D:0E and the 'Link State' is 10000MBit Full-Duplex.

Network Configuration	
Control Media1 Media2	
IP Address Type DHCP	
IP Address	172.16.250.3
Netmask	255.255.0.0
Default Gateway	0.0.0.0
MAC Address	00:0C:17:88:1D:0E
Link State	10000MBit Full-Duplex

The Network screen allows you to view and change your IP Mini-Converter's network settings. Click Apply to activate any changes.

IP Address Type - IP Address Type determines the type of TCP/IP network configuration to be used. DHCP enables connecting to the network DHCP server, which assigns the IP Address, Netmask, and Gateway automatically. Static lets you set these parameters manually.

NOTE: If the IP Address Type is DHCP, the IP Address, Netmask, and Default Gateway are gray, indicating they are set automatically and cannot be changed unless IP Address Type is first set to Static. Changes are saved and activated upon confirmation using the Apply button.

- **DHCP** (default) - Selects automatic IP address assignment from the LAN DHCP server. If a DHCP server cannot be found, it fails over to the static IP address.
- **Static** - Assigns a static IP address manually. The factory default static IP address: 192.168.0.1.

IP Address - IP Address determines a static IP address to be used for TCP/IP networking. Consult your network administrator about how to set this value.

- If IP Address Type is set to DHCP, the IP address is set automatically by the network DHCP server and cannot be entered here.
- If IP Address Type is set to Static, enter an IP address compatible with your LAN here. Also enter a netmask and default gateway address in the following two parameters. Click Apply when you are ready to apply all three entries.
- If IP Address Type is set to DHCP and there is a DHCP failure, the IP address is set to the static IP address.

Netmask - Netmask determines the subnet mask to be used for TCP/IP networking.

- Enter a subnet mask compatible with your LAN. This is only needed for Static IP configurations. The factory default Subnet Mask is 255.255.255.0
- If IP Address Type is set to DHCP, the Subnet Mask is set by the DHCP server and cannot be changed by the user.

Default Gateway - Default Gateway determines the gateway or router used on your LAN for TCP/IP networking.

Without a properly configured default gateway (whether you have a router/gateway or not), your IP Mini-Converter will be unable to see other IP Mini-Converters on the network, although you may still be able to control this IP Mini-Converter via a web browser. Also, without a proper gateway defined, the discovery feature on the Network web page will not list other units on the network.


- Enter a default gateway or router address. This is only needed for Static IP configurations. The factory Default Gateway is 192.168.0.1.
- If IP Address Type is set to DHCP, the Default Gateway is set by the DHCP server and cannot be changed by the user.

MAC Address - Reports the connected IP Mini-Converter's Media Access Control Address.

Link State - Reports the current status of the Ethernet connection.

Firmware Screen

Figure 23. IPR-10G2-HDMI Firmware Screen



Downloading and Installing Updated Firmware

The Update Firmware screen allows you to download and install a firmware update from AJA.

To Download and Install Updated Firmware

1. Visit the AJA website (aja.com) to locate and download the updated software. The following page provides support information and will include links to locations where you can download updates:
<https://www.aja.com/products/mini-converters/ip-converters#support>
2. After downloading the software update to your local drive, use the Browse or Choose File button to locate the local software copy.
3. Follow the prompts to load the new firmware into your unit.
4. After the firmware has finished installing, reboot the unit by disconnecting power for a few seconds, then reconnecting power.

NOTE: You can also update the firmware using eMini-Setup. See "Firmware Update Procedure" on page 18 for details.

Booting the 10 GigE IP Mini-Converters from the Safeboot Firmware

The 10 GigE IP Mini-Converters contain primary firmware and safeboot (secondary) firmware. To boot from the primary firmware, just cycle the unit's power.

In the event that the primary firmware becomes corrupted, you can boot the unit using the safeboot firmware.

To Boot from the Safeboot Firmware

1. Remove power from the device.
2. Using a very narrow tool, such as the end of a paper clip, press down and hold the recessed safeboot button, making sure you feel the button depress. The recessed safeboot button is located next to the Control LAN port.


Figure 24. Location of recessed safeboot button



3. While keeping the safeboot button depressed, apply power, then continue holding down the safeboot button for three seconds.

4. Remove the paper clip from the safeboot button. The unit will boot from the safeboot firmware. After rebooting, the message "Safeboot" displays under the Alarms heading.


Figure 25. The Safeboot alarm message



5. Finally, update the firmware as described above under ["Downloading and Installing Updated Firmware" on page 33](#).

Following a successful firmware update and reboot, the message "None" displays under the Alarms heading.

Figure 26. The alarm message after a successful firmware update



Appendix A – Frequently Asked Questions

What ANC data is supported when using IPR-10G2-HDMI for receiving and decoding?

No ANC data support at this time.

Is PTP required when using the IPR-10G2-HDMI?

No, but an ST 2059 compliant PTP clock is recommended.

How many channels of analog audio can be output or monitored by the IPR-10G2-HDMI for decoding?

2

Does IPR-10G2-HDMI support NMOS?

Yes, IPR-10G2-HDMI supports NMOS Receive according to standards IS-04 v1.2 and IS-05 v1.0.

Is Ember Plus supported with IPR-10G2-HDMI?

Yes, IPR-10G2-HDMI supports the latest version of Ember+ SDK (v1.6.2).

Is IPR-10G2-HDMI able to receive video streams from either Narrow or Wide senders in either "Linear" or "Gap" Mode as defined in SMPTE ST 2110-21 spec?

Yes, the IPR-10G2-HDMI can receive Wide and Narrow in either "Linear" or "Gap" Mode.

Is IPR-10G2-HDMI compliant with SMPTE ST 2059-1, standard to derive video audio and time references using the SMPTE Epoch (Jan 1, 1970, 00:00 GMT)?

Yes, IPR-10G2-HDMI is compliant with SMPTE ST 2059-1.

Is IPR-10G2-HDMI compatible with PTP PTPv2 / IEEE 1588-2008?

Yes, IPR-10G2-HDMI is compliant with PTP PTPv2 / IEEE 1588-2008.

Can I use either Unicast or Multicast setups with IPT or IPR products?

Yes

Do I have to use a network switch when working with combinations of IPR-10G2-HDMI units?

You do not have to use a switch, as IPT to IPR connections can be point-to-point.

NOTE: You will need to use a switch if you are intending to take advantage of multicast and/or routing transmission data to multiple destinations.

Is it possible to send a SMPTE 2110 signal direct from a KONA IP to an IPR-10G2-HDMI without using a switch?

Yes

Are IPR-10G2-HDMI and IPR-10G2-SDI discoverable over a network with both macOS and Windows?

On Windows, yes. 10 GigE IP Mini-Converters are shipped from the factory with UPnP (Universal Plug and Play) services enabled, so they are discoverable through Windows Explorer (for networked Windows PCs).

On macOS versions later than El Capitan, this functionality through Bonjour is no longer supported. Alternatively, try going to System Preferences > Sharing, and turn on File Sharing.

If you find that the version of macOS that you are using does not support discovery via your network, we recommend using eMini-Setup via USB to a local host to set up the initial configuration – which will subsequently allow you to discover the device via the IP address you set.

Appendix B – Specifications

IPR-10G2-HDMI Tech Specs

Video Formats

- (HD) 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1920x1080i 50, 59.94
- (HD) 1280x720p 50, 59.94, 60
- (SD) 625i 50
- (SD) 525i 59.94

Video Quality

- 10-bit, 4:2:2, uncompressed

Discovery, Registration and Control

- NMOS
- Ember Plus (no discovery, control only)

Media Transport Interfaces

- SMPTE ST 2110
 - 2x SFP+ Cages - SFPs not included
- Recommended 10 GigE SFP+ modules:
 - Arista Networks SFP-10G-SR Compatible 10GBASE-SR
 - Fiberstore SFP-10GSR-85 10G SFP+ 850nm
 - Finisar FTLX1471D3BCL (for single mode 1310nm)
 - Mellanox MFM1T02A-SR 850nm 10G

NOTE: Maximum supported SFP+ power is 500 mW per SFP+ cage

Video Input IP

- SMPTE ST 2110
 - Single channel input
 - Dual channel input for hitless switching (based on SMPTE 2022-7)

Video Output Digital

- 1x HDMI Standard Type A connector
 - HDMI v1.4b 24/30-bits per pixel, RGB/YUV

Audio Output Digital

- Up to 8-Channel, HDMI embedded audio, 24-bit per channel, 48 kHz synchronous

Audio Output Analog

- 2x RCA analog audio
 - Levels at -10 dBu (nominal)

Reference

- 1x BNC
 - Reserved for Future Potential Features

User Controls

- 1x RJ-45 for 10/100/1000 Base-T Ethernet
 - Web and REST clients supported
- 1x USB 2.0 Mini-B connector
 - AJA eMini-Setup of network parameters via local desktop computer

Size (w x d x h)

- 5.07" x 0.94" x 5.06" (128.8mm x 23.9mm x 128.4mm)

Weight

- 0.6 lb (0.3 kg)

Power

- 5-20VDC Regulated, 13 Watts, Power supply required (DWP-U-R1 included with purchase)

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% non-condensing
- Operating Altitude: <3,000 meters (<10,000 feet)

IPR-10G2-SDI Tech Specs

Video Formats

- (HD) 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1920x1080i 50, 59.94
- (HD) 1280x720p 50, 59.94, 60
- (SD) 625i 50
- (SD) 525i 59.94

Video Quality

- 10-bit, 4:2:2, uncompressed

Discovery, Registration and Control

- NMOS
- Ember Plus (no discovery, control only)

Media Transport Interfaces

- SMPTE ST 2110
 - 2x SFP+ Cages - SFPs not included
- Recommended 10 GigE SFP+ modules:
 - Arista Networks SFP-10G-SR Compatible 10GBASE-SR
 - Fiberstore SFP-10GSR-85 10G SFP+ 850nm
 - Finisar FTLX1471D3BCL (for single mode 1310nm)
 - Mellanox MFM1T02A-SR 850nm 10G

NOTE: Maximum supported SFP+ power is 500 mW per SFP+ cage

Video Input IP

- SMPTE ST 2110
 - Single channel input
 - Dual channel input for hitless switching (based on SMPTE 2022-7)

Video Output Digital

- 2x 3G SDI BNC (single source, mirrored output)
- 4:2:2 10-bits/pixel (embedded audio)

Audio Output Digital

- Up to 8-Channel, SDI embedded audio, 24-bit per channel, 48 kHz synchronous

Audio Output Analog

- 2x RCA analog audio
 - Levels at -10 dBu (nominal)

Reference

- 1x BNC
 - Reserved for Future Potential Features

User Controls

- 1x RJ-45 for 10/100/1000 Base-T Ethernet
 - Web and REST clients supported
- 1x USB 2.0 Mini-B connector
 - AJA eMini-Setup of network parameters via local desktop computer

Size (w x d x h)

- 5.07" x 0.94" x 5.06" (128.8mm x 23.9mm x 128.4mm)

Weight

- 0.6 lb (0.3 kg)

Power

- 5-20VDC Regulated, 13 Watts, Power supply required (DWP-U-R1 included with purchase)

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% non-condensing
- Operating Altitude: <3,000 meters (<10,000 feet)

Appendix C – Safety and Compliance

Federal Communications Commission (FCC) Compliance Notices

Class A Interference Statement

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15, Subpart B of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Canadian ICES Statement

Canadian Department of Communications Radio Interference Regulations

This digital apparatus does not exceed the Class A limits for radio-noise emissions from a digital apparatus as set out in the Radio Interference Regulations of the Canadian Department of Communications. This Class A digital apparatus complies with Canadian ICES-003.

Règlement sur le brouillage radioélectrique du ministère des Communications

Cet appareil numérique respecte les limites de bruits radioélectriques visant les appareils numériques de classe A prescrites dans le Règlement sur le brouillage radioélectrique du ministère des Communications du Canada. Cet appareil numérique de la Classe A est conforme à la norme NMB-003 du Canada.

European Union and European Free Trade Association (EFTA) Regulatory Compliance

This equipment may be operated in the countries that comprise the member countries of the European Union and the European Free Trade Association. These countries, listed in the following paragraph, are referred to as The European Community throughout this document:

AUSTRIA, BELGIUM, BULGARIA, CYPRUS, CZECH REPUBLIC, DENMARK, ESTONIA, FINLAND, FRANCE, GERMANY, GREECE, HUNGARY, ICELAND, IRELAND, ITALY, LATVIA, LICHENSTEIN, LITHUANIA, LUXEMBOURG, MALTA, NETHERLANDS, NORWAY, POLAND, PORTUGAL, ROMANIA, SLOVAKIA, SLOVENIA, SPAIN, SWEDEN, SWITZERLAND, UNITED KINGDOM

Declaration of Conformity

Marking by this symbol indicates compliance with the Essential Requirements of the EMC Directive of the European Union 2014/30/EU.



This equipment meets the following conformance standards:

Safety

EN 60065: 2014 (T-Mark License),

IEC 60065: 2014 (CB Scheme Report/Certificate)

Additional licenses issued for specific countries available on request.

Emissions

EN 55032: 2012 + AC: 2013, CISPR 32: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013

Immunity

EN 55103-2: 2009, EN 61000-4-2:2009, EN 61000-4-3:2006+A1:2008+A2:2010,

EN 61000-4-4:2004+A1:2010, EN 61000-4-5:2006, EN 61000-4-6:2009,

EN 61000-4-11:2004

Environments: E2, E3 and E4

The product is also licensed for additional country specific standards as required for the International Marketplace.



Warning! This is a Class A product. In a domestic environment, this product may cause radio interference, in which case, the user may be required to take appropriate measures.

Achtung! Dieses ist ein Gerät der Funkstörgrenzwertklasse A. In Wohnbereichen können bei Betrieb dieses Gerätes Rundfunkstörungen auftreten, in welchen Fällen der Benutzer für entsprechende Gegenmaßnahmen verantwortlich ist.

Attention! Ceci est un produit de Classe A. Dans un environnement domestique, ce produit risque de créer des interférences radioélectriques, il appartiendra alors à l'utilisateur de prendre les mesures spécifiques appropriées..

Recycling Notice



This symbol on the product or its packaging indicates that this product must not be disposed of with your other household waste. Instead, it is your responsibility to dispose of your waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop off your waste for recycling, please contact your local authority, or where you purchased your product.

Korea KCC Compliance Statement

A급 기기 (업무용 방송통신기자재)	이 기기는 업무용(A급) 전자파적합기기로서 판매자 또는 사용자는 이 점을 주의하시기 바라며, 가정외의 지역에서 사용하는 것을 목적으로 합니다.
Class A (Broadcasting Communication Equipment for Office Use)	As an electromagnetic wave equipment for office use (Class A), this equipment is intended to use in other than home area. Sellers or users need to take note of this.

Taiwan Compliance Statement

警告使用者：

這是甲類的資訊產品，在居住的環境中使用時，可能會造成射頻干擾，在這種情況下，使用者會被要求採取某些適當的對策。

This is a Class A product based on the standard of the Bureau of Standards, Metrology and Inspection (BSMI) CNS 13438, Class A. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Japan Compliance Statement

この装置は、クラスA情報技術装置です。この装置を家庭環境で使用すると電波妨害を引き起こすことがあります。この場合には使用者が適切な対策を講ずるよう要求されることがあります。 VCCI-A

This is a Class A product based on the standard of the VCCI Council (VCCI 32: 2016). If this equipment is used in a domestic environment, radio interference may occur, in which case, the user may be required to take corrective actions.

Translated Warning and Caution Messages

The following caution statements, warning conventions, and warning messages apply to this product and manual.



Warning Symbol



Caution Symbol

Before Operation Please Read These Instructions



Warning! Read and follow all warning notices and instructions marked on the product or included in the documentation.

Avertissement! Lisez et conformez-vous à tous les avis et instructions d'avertissement indiqués sur le produit ou dans la documentation.

Warnung! Lesen und befolgen Sie die Warnhinweise und Anweisungen, die auf dem Produkt angebracht oder in der Dokumentation enthalten sind.

¡Advertencia! Lea y siga todas las instrucciones y advertencias marcadas en el producto o incluidas en la documentación.

Aviso! Leia e siga todos os avisos e instruções assinalados no produto ou incluídos na documentação.

Avviso! Leggere e seguire tutti gli avvisi e le istruzioni presenti sul prodotto o inclusi nella documentazione.



Warning! Do not use this device near water and clean only with a dry cloth.

Avertissement! N'utilisez pas cet appareil près de l'eau et nettoyez-le seulement avec un tissu sec..

Warnung! Das Gerät nicht in der Nähe von Wasser verwenden und nur mit einem trockenen Tuch säubern.

¡Advertencia! No utilice este dispositivo cerca del agua y límpielo solamente con un paño seco.

Aviso! Não utilize este dispositivo perto da água e limpe-o somente com um pano seco.

Avviso! Non utilizzare questo dispositivo vicino all'acqua e pulirlo soltanto con un panno asciutto.



Warning! Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.

Avertissement! Ne bloquez aucune ouverture de ventilation. Suivez les instructions du fabricant lors de l'installation.

Warnung! Die Lüftungsöffnungen dürfen nicht blockiert werden. Nur gemäß den Anweisungen des Herstellers installieren.

¡Advertencia! No bloquee ninguna de las aberturas de la ventilación. Instale de acuerdo con las instrucciones del fabricante.

Aviso! Não obstrua nenhuma das aberturas de ventilação. Instale de acordo com as instruções do fabricante.

Avviso! Non ostruire le aperture di ventilazione. Installare in conformità con le istruzioni del fornitore.



Warning! Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.

Avertissement! N'installez pas l'appareil près d'une source de chaleur telle que des radiateurs, des bouches d'air de chauffage, des fourneaux ou d'autres appareils (amplificateurs compris) qui produisent de la chaleur.

Warnung! Nicht in der Nähe von Wärmequellen wie Heizkörpern, Heizregistern, Öfen oder anderen Wärme erzeugenden Geräten (einschließlich Verstärkern) aufstellen.

¡Advertencia! No instale cerca de fuentes de calor tales como radiadores, registros de calor, estufas u otros aparatos (incluidos amplificadores) que generan calor.

Aviso! Não instale perto de nenhuma fonte de calor tal como radiadores, saídas de calor, fogões ou outros aparelhos (incluindo amplificadores) que produzam calor.

Avviso! Non installare vicino a fonti di calore come termosifoni, diffusori di aria calda, stufe o altri apparecchi (amplificatori compresi) che emettono calore



Warning! Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.

Avertissement! La sécurité de la prise polarisée ou de la prise de type mise à la terre ne doit en aucun cas être empêchée de fonctionner. Une prise polarisée a deux broches, l'une étant plus large que l'autre. Une prise de type mise à la terre a deux broches et une troisième broche pour la mise à la terre. La broche large ou la troisième broche sont fournies pour votre sécurité. Si la prise fournie ne s'insère pas dans votre prise femelle, consultez un électricien pour le remplacement de la prise femelle obsolète.

Warnung! Der Sicherheitszweck des gepolten bzw. Schukosteckers ist zu berücksichtigen. Ein gepolter Stecker verfügt über zwei Pole, von denen einer breiter als der andere ist. Ein Schukostecker verfügt neben den zwei Polen noch über einen dritten Pol zur Erdung. Der breite Pol bzw. der Erdungspol dienen der Sicherheit. Wenn der zur Verfügung gestellte Stecker nicht in Ihren Anschluss passt, konsultieren Sie einen Elektriker, um den veralteten Anschluss zu ersetzen.

¡Advertencia! No eche por tierra la finalidad del tipo de enchufe polarizado con conexión a tierra. Un enchufe polarizado tiene dos espigas, una más ancha que la otra. Un enchufe con conexión a tierra tiene dos espigas iguales y una tercera espiga que sirve para la conexión a tierra. La espiga ancha, o la tercera espiga, sirven para su seguridad. Si el enchufe suministrado no encaja en el tomacorriente, consulte con un electricista para reemplazar el tomacorriente obsoleto.

Aviso! Não anule a finalidade da segurança da ficha polarizada ou do tipo ligação terra. Uma ficha polarizada tem duas lâminas sendo uma mais larga do que a outra. Uma ficha do tipo de ligação à terra tem duas lâminas e um terceiro terminal de ligação à terra. A lâmina larga ou o terceiro terminal são fornecidos para sua segurança. Se a ficha fornecida não couber na sua tomada, consulte um electricista para a substituição da tomada obsoleta.

Avviso! Non compromettere la sicurezza della spina polarizzata o con messa a terra. Una spina polarizzata ha due spinotti, di cui uno più largo. Una spina con messa a terra ha due spinotti e un terzo polo per la messa a terra. Lo spinotto largo o il terzo polo sono forniti per motivi di sicurezza. Se la spina fornita non si inserisce nella presa di corrente, contattare un elettricista per la sostituzione della presa obsoleta.



Warning! Since the Mains plug is used as the disconnection for the device, it must remain readily accessible and operable.

Avertissement! Puisque la prise principale est utilisée pour débrancher l'appareil, elle doit rester aisément accessible et fonctionnelle.

Warnung! Da der Netzstecker als Trennvorrichtung dient, muss er stets zugänglich und funktionsfähig sein.

¡Advertencia! Puesto que el enchufe de la red eléctrica se utiliza como dispositivo de desconexión, debe seguir siendo fácilmente accesible y operable.

Aviso! Dado que a ficha principal é utilizada como a desconexão para o dispositivo, esta deve manter-se prontamente acessível e funcional.

Avviso! Poiché il cavo di alimentazione viene usato come dispositivo di sconnessione, deve rimanere prontamente accessibile e operabile.



Warning! Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the device.

Avertissement! Protégez le cordon d'alimentation pour que l'on ne marche pas dessus ou qu'on le pince, en particulier au niveau des prises mâles, des réceptacles de convenance, et à l'endroit où il sort de l'appareil.

Warnung! Vermeiden Sie, dass auf das Netzkabel getreten oder das Kabel geknickt wird, insbesondere an den Steckern, den Steckdosen und am Kabelausgang am Gerät.

¡Advertencia! Proteja el cable de energía para que no se le pise ni apriete, en especial cerca del enchufe, los receptáculos de conveniencia y el punto del que salen del equipo.

Aviso! Proteja o cabo de alimentação de ser pisado ou de ser comprimido particularmente nas fichas, em tomadas de parede de conveniência e no ponto de onde sai do dispositivo.

Avviso! Proteggere il cavo di alimentazione in modo che nessuno ci cammini sopra e che non venga schiacciato soprattutto in corrispondenza delle spine e del punto in cui esce dal dispositivo.



Warning! Unplug this device during lightning storms or when unused for long periods of time.

Avertissement! Débranchez cet appareil pendant les orages avec éclairs ou s'il est inutilisé pendant de longues périodes.

Warnung! Das Gerät ist bei Gewitterstürmen oder wenn es über lange Zeiträume ungenutzt bleibt vom Netz zu trennen.

¡Advertencia! Desenchufe este dispositivo durante tormentas eléctricas o cuando no se lo utilice por largos periodos del tiempo.

Aviso! Desconecte este dispositivo da tomada durante trovoadas ou quando não é utilizado durante longos períodos de tempo.

Avviso! Utilizzare soltanto i collegamenti e gli accessori specificati e/o venduti dal produttore, quali il treppiedi e l'esoscheletro.



Warning! Refer all servicing to qualified service personnel. Servicing is required when the device has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the device, the device has been exposed to rain or moisture, does not operate normally, or has been dropped.

Avertissement! Référez-vous au personnel de service qualifié pour tout entretien. L'entretien est exigé quand l'appareil a été endommagé de quelque manière que ce soit, par exemple lorsque le cordon d'alimentation ou la prise sont endommagés, que du liquide a été versé ou des objets sont tombés dans l'appareil, que l'appareil a été exposé à la pluie ou à l'humidité, ne fonctionne pas normalement ou est tombé.

Warnung! Das Gerät sollte nur von qualifizierten Fachkräften gewartet werden. Eine Wartung ist fällig, wenn das Gerät in irgendeiner Weise beschädigt wurde, wie bei beschädigtem Netzkabel oder Netzstecker, falls Flüssigkeiten oder Objekte in das Gerät gelangen, das Gerät Regen oder Feuchtigkeit ausgesetzt wurde, nicht ordnungsgemäß funktioniert oder fallen gelassen wurde.

¡Advertencia! Consulte al personal calificado por cuestiones de reparación. El servicio de reparación se requiere cuando el dispositivo ha recibido cualquier tipo de daño, por ejemplo cable o espigas dañadas, se ha derramado líquido o se han caído objetos dentro del dispositivo, el dispositivo ha sido expuesto a la lluvia o humedad, o no funciona de modo normal, o se ha caído.

Aviso! Remeta todos os serviços de manutenção para o pessoal de assistência qualificado. A prestação de serviços de manutenção é exigida quando o dispositivo foi danificado mediante qualquer forma, como um cabo de alimentação ou ficha que se encontra danificado/a, quando foi derramado líquido ou caíram objectos sobre o dispositivo, quando o dispositivo foi exposto à chuva ou à humidade, quando não funciona normalmente ou quando foi deixado cair.

Avviso! Fare riferimento al personale qualificato per tutti gli interventi di assistenza. L'assistenza è necessaria quando il dispositivo è stato danneggiato in qualche modo, ad esempio se il cavo di alimentazione o la spina sono danneggiati, è stato rovesciato del liquido è stato rovesciato o qualche oggetto è caduto nel dispositivo, il dispositivo è stato esposto a pioggia o umidità, non funziona correttamente o è caduto



Warning! Do not open the chassis. There are no user-serviceable parts inside. Opening the chassis will void the warranty unless performed by an AJA service center or licensed facility.

Avertissement! Ne pas ouvrir le châssis. Aucun élément à l'intérieur du châssis ne peut être réparé par l'utilisateur. La garantie sera annulée si le châssis est ouvert par toute autre personne qu'un technicien d'un centre de service ou d'un établissement agréé AJA.

Warnung! Öffnen Sie das Gehäuse nicht. Keine der Geräteteile können vom Benutzer gewartet werden. Durch das Öffnen des Gehäuses wird die Garantie hinfällig, es sei denn, solche Wartungsarbeiten werden in einem AJA-Service-Center oder einem lizenzierten Betrieb vorgenommen.

¡Advertencia! No abra el chasis. El interior no contiene piezas reparables por el usuario. El abrir el chasis anulará la garantía a menos que se lo haga en un centro de servicio AJA o en un local autorizado.

Advertência! Não abra o chassi. Não há internamente nenhuma peça que permita manutenção pelo usuário. Abrir o chassi anula a garantia, a menos que a abertura seja realizada por uma central de serviços da AJA ou por um local autorizado.

Avvertenza! Non aprire lo chassis. All'interno non ci sono parti riparabili dall'utente. L'apertura dello chassis invaliderà la garanzia se non viene effettuata da un centro ufficiale o autorizzato AJA.



Warning! Disconnect the external AC power supply line cord(s) from the mains power before moving the unit.

Avertissement! Retirez le ou les cordons d'alimentation en CA de la source d'alimentation principale lorsque vous déplacez l'appareil.

Warnung! Trennen Sie die Wechselstrom-Versorgungskabel vom Netzstrom, bevor Sie das Gerät verschieben.

¡Advertencia! Cuando mueva la unidad desenchufe de la red eléctrica el/los cable(s) de la fuente de alimentación CA tipo brick.

Advertência! Remova os cabos CA de alimentação brick da rede elétrica ao mover a unidade.

Avvertenza! Scollegare il cavo dell'alimentatore quando si sposta l'unità.



Warning! Only use attachments and accessories specified and/or sold by the manufacturer.

Avertissement! Utilisez seulement les attaches et accessoires spécifiés et/ou vendus par le fabricant.

Warnung! Verwenden Sie nur Zusatzgeräte und Zubehör angegeben und / oder verkauft wurde durch den Hersteller.

¡Advertencia! Utilice solamente los accesorios y conexiones especificados y/o vendidos por el fabricante.

Aviso! Utilize apenas equipamentos/acessórios especificados e/ou vendidos pelo fabricante.

Avviso! Utilizzare soltanto i collegamenti e gli accessori specificati e/o venduti dal produttore.

Warranty and Liability Information

AJA VIDEO SYSTEMS, INC.

Limited Warranty on Hardware

AJA Video Systems, Inc. (AJA Video) warrants that the hardware product, not including storage modules or software components, will be free from defects in materials and workmanship for a period of five (5) years from the date of purchase. AJA Video warrants that the storage modules provided as part of the hardware product will be free from defects in materials and workmanship for a period of one year from the date of purchase. AJA Video provides a separate software warranty as part of the license agreement applicable to software components.

If a hardware product or storage module (hereafter, a “product”) proves to be defective during the applicable warranty period, AJA Video, at its option, will either repair the defective product without charge for parts and labor, or will provide a replacement in exchange for the defective product.

To obtain service under this warranty, the Customer must notify AJA Video of the defect before expiration of the warranty period and make suitable arrangements for the performance of service by contacting AJA Video support through the channels set forth on the support contacts web page at <http://www.aja.com/support>. Except as stated, the Customer shall bear all shipping, packing, insurance and other costs, excluding parts and labor, to effectuate repair. Customer shall pack and ship the defective product to a service center designated by AJA Video, with shipping charges prepaid. AJA Video shall pay to return the product to Customer but only if to a location within the country in which the AJA Video service center is located.

This warranty shall not apply to any defect, failure or damage caused by negligent, inadequate or improper use, handling or maintenance. Without limiting the foregoing, AJA Video shall not be obligated to furnish service under this warranty or repair any damage or malfunction a) resulting from attempts by personnel other than AJA Video representatives to install, repair or service the product, b) resulting from improper use or connection to incompatible equipment, c) caused by the use of non-AJA Video parts or supplies, d) if the product has been modified or integrated with other products when the effect of such a modification or integration increases the time or difficulty of servicing the product, or e) resulting from being dropped or otherwise subjected to undue force, exposure to moisture or other corrosive or conductive substances, exposure to strong magnetic fields, use with improperly regulated power supplies, exposure to electric shock, use in temperatures outside the specified operating range, or otherwise failing to treat the product in accordance with the standard of care appropriate to sensitive and delicate electronic equipment.

EXCEPT AS STATED ABOVE, AJA VIDEO AND ITS VENDORS DISCLAIM IN THEIR ENTIRETY ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ALL WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. AJA VIDEO'S RESPONSIBILITY TO REPAIR OR REPLACE TIMELY REPORTED DEFECTIVE PRODUCTS IS THE WHOLE AND EXCLUSIVE REMEDY CUSTOMER IS PROVIDED WITH RESPECT TO HARDWARE PRODUCTS AND THEIR STORAGE MODULES. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES OR LIMITATIONS ON APPLICABLE STATUTORY RIGHTS OF A CONSUMER, SO SOME OR ALL OF THE TERMS OF THIS PARAGRAPH MAY NOT APPLY TO YOU.

THE PRODUCT IS NOT INTENDED, STATED, OR WARRANTED TO OPERATE UNINTERRUPTED OR ERROR-FREE. YOU UNDERSTAND AND ACKNOWLEDGE THAT THE PRODUCT IS NOT INTENDED TO BE USED AS THE SOLE OR PRIMARY DATA SOURCE OR TARGET FOR CRITICAL DATA, AND THAT IT IS YOUR RESPONSIBILITY TO IMPLEMENT REDUNDANT CAPTURE AND BACKUP SYSTEMS AS APPROPRIATE.

Limitation of Liability

Under no circumstances shall AJA video BE LIABLE IN ANY WAY FOR ANY LOST, CORRUPTED OR DESTROYED DATA, FOOTAGE OR WORK, OR FOR ANY OTHER INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LOST PROFITS, OR FOR ANY THIRD PARTY CLAIM, IN CONNECTION WITH THE PRODUCT, WHETHER RESULTING FROM DEFECTS IN THE PRODUCT, SOFTWARE OR HARDWARE FAILURE, OR ANY OTHER CAUSE WHATSOEVER, EVEN IF AJA VIDEO HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. AJA VIDEO'S LIABILITY IN CONNECTION WITH THE PRODUCT SHALL UNDER NO CIRCUMSTANCES EXCEED THE PURCHASE PRICE PAID FOR THE PRODUCT. The foregoing limitations apply even if any remedy set forth in this LIMITED WARRANTY fails of its essential purpose. SOME JURISDICTIONS DO NOT ALLOW THE LIMITATION OF LIABILITY FOR PERSONAL INJURY, OR OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO SOME OR ALL OF THE TERMS OF THIS PARAGRAPH MAY NOT APPLY TO YOU.

Governing Law and Language; Your Rights.

This limited warranty is the only warranty provided by AJA Video on the hardware product. It supersedes all prior or contemporaneous understandings regarding such subject matter. No amendment to or modification of this warranty will be binding unless in writing and signed by AJA Video. The laws of the State of California, USA will govern this warranty and any dispute arising from it. Any translation of this Agreement is intended for convenience and to meet local requirements and in the event of a dispute between the English and any non-English versions, the English version of this warranty will govern. This limited warranty gives you specific legal rights and you may have other rights that vary from jurisdiction to jurisdiction, some of which are noted above.

Index

A

- AJA Support 2
- Audio 5
 - RCA Analog Audio Output 5, 28
- Authentication 20
 - Disabling 19
 - Enabling or Disabling 24

B

- Block Diagram 7

C

- Cable
 - Disconnecting USB Cable 9
 - Ethernet 9, 20
 - USB Cable Supplied 13
- Compliance 40
- Config Screen 24
- Configuration
 - Initial 6, 7, 8, 9, 11

D

- Decoding 5, 9
- DHCP
 - Assigned IP Address 11
 - Controlling Computer's Ethernet Port 20
 - Enabled 9
 - Failure 31
 - IP Address 8, 15, 16, 17
 - Server 9
 - Setting IP Address Type for Media LAN Port 31

E

- eMini-Setup 6, 7, 8, 9, 11
 - Acquiring 11
 - Documentation 11
 - Downloading 11
 - Installing 12
 - Operating 14
 - Running 13
 - Screen 14

F

- Features 6
- Firmware
 - Corrupted 33
 - Downloading 33
 - Installing New 18
 - Loading 11
 - Safeboot 33
 - Screen, Web UI 32
 - Status 23
 - Update Procedure 18
 - Updating from Web UI 33

Version Installed 15

H

- HDMI
 - Embedded Audio 5

I

- Installation
 - eMini-Setup on Mac 13
 - eMini-Setup on Windows 12
 - Initial 9
 - Of Firmware Using eMini-Setup 18
 - Overview 8
- I/O Connections 7
- IP Address 20
 - Accessing Settings Through eMini-Setup 11
 - Applying Changes with eMini-Setup 15
 - Assigning from DHCP Server 31
 - Assigning Static 31
 - Choosing DHCP or Static with eMini-Setup 15
 - Determining 8, 9
 - Determining Type in Web UI 31
 - DHCP Server Assigning 9
 - Factory Default Static 31
 - Media LAN Port 20
 - Using to Access Web UI 11, 20

L

- LAN
 - Behavior of Control LAN LEDs 8
 - Connecting Unit to Network with Control LAN and Media LAN 9
 - Entering Compatible IP Address 31
 - Using Control LAN to Make Configuration Changes 9
 - Using Media LAN for Control and Media 9, 20
 - Using Media LAN for Incoming Media 9
 - Using Standard RJ-45 Connector 20
 - Using Web UI Network Screen to Access Control LAN Port Settings 30
- LED Behavior
 - Ready, Lock and LAN 8

N

- Network Configuration
 - Accessing Control and Media Parameters Through Media LAN Only 9
 - Initial Installation 9
 - IP Address Type 31

Network Screen

- Configuring Settings for Control LAN Ethernet Port 30
- Configuring Settings for Media LAN Ethernet Port 30, 31

O

- Overview
 - eMini-Setup 11
 - Installation 8
 - Remote Control 20
 - Web Interface 20

P

- Presets
 - Changing Name 29
 - Erasing 30
 - Exporting 29, 30
 - File Name Suffix 30
 - Importing 30
 - Recalling 29
 - Register 29
 - Saving 29
 - Screen 29
 - Screen Controls 29

R

- Remote Control 6
 - Overview 20
- RJ-45
 - Connector 20

S

- Safety and Compliance 40
- Serial Number 15
- Specifications 37
 - Technical 37
- Status
 - eMini-Setup Application 15
 - Ethernet Connection 32
 - Firmware 23
 - Input 23
 - Network 23
 - Screen 23
- Subnet Mask
 - Determined by Netmask 32
 - eMini-Setup 15, 16, 17
 - Factory Default 32

T

- Technical Support 2

U

- Update
 - Firmware Screen 33
- Updated

- Documentation 11
- Updated Software
 - Downloading 33
- Update Procedure
 - Firmware 18
- Update Tab 18
 - Installing New Firmware 18
- USB Cable
 - Running eMini-Setup 13
- USB Connection
 - Working with eMini-Setup 8
- USB Port
 - Connecting to Unit from Controlling Computer 11
 - Firmware Update Procedure 18
 - Required for Initial Configuration Using eMini-Setup 7, 11
- User Authentication
 - Enabling or Disabling for Web Interface 24

W

- Web Browser
 - Accessing Unit Through Its IP Address 9, 11
 - Accessing User Interface 8
 - Loading Firmware 11
 - Preferred 7
 - System Requirements 7
- Web Server
 - Access Password 30
 - Built In 6, 11, 20
 - Unit's Internal 7