

# AJA MiniConfig Release Notes - v2.11.0

## Control Software for AJA Mini-Converters

### General

---

This version of MiniConfig adds support for the newly released HA5-4K Mini-Converter. Users of AJA Mini-Converters other than the HA5-4K and UDC will not gain new functionality with this version of MiniConfig, however it is recommended to migrate to the most recent version even when using non-updated Mini-Converters.

### New Mini-Converters

---

#### HA5-4K

The HA5-4K is a 4K HDMI to Quad Link 4K SDI converter with support for input and output up to 50/60 fps.

### Improvements

---

#### UDC

Improve audio detection of 2-channel mode upon hot-plug detect

### Installing the Latest Software

---

Mini-Converters come from the factory with the most current version of firmware pre-installed. To get the latest version of MiniConfig, visit the AJA website support area and select your Mini-Converter from the list:

<https://www.aja.com/en/category/mini-converters#support>

The MiniConfig software can be found in the Software section of the support page for your Mini-Converter. Previous releases of the AJA MiniConfig software are also available in the Software Archive section for each supported Mini-Converter.

### Firmware Upgrade Procedure

---

The manual provided with your AJA Mini-Converter describes the firmware update process; please refer to it in order to properly update your firmware. The product manuals are also installed with the software in the /AJA/MiniConfig/Documentation/ folder.

Individual product manuals are available online for download from the Mini-Converter section of the AJA website:

<http://www.aja.com/en/support/>

## Products Supported In This Release

---

3G-AM	Hi5-4K
LUT-box	HA5-4K
Hi5-3D	4K2HD
Hi5-3G	V2Digital
HDP2	V2Analog
UDC	Hi5-Plus
ROI	HA5-Plus
3G-AMA	