

AJA eMini-Setup v2.4.4 for Windows - Release Notes

Windows Control Software for AJA Mini-Converters, HELO Plus, HELO, ColorBox, DANTE-12GAM, IP25-R, and KUMO Routers and Control Panels

Introduction

eMini-Setup is AJA's compact utility for configuring network settings and applying firmware updates across the following AJA devices:

- AJA HELO Plus
- AJA HELO
- AJA ColorBox
- AJA DANTE-12GAM
- AJA IPT-10G2-HDMI, IPT-10G2-SDI, IPR-10G2-HDMI, IPR-10G2-SDI, IPR-10G-HDMI
- AJA IPT-1G-HDMI, IPT-1G-SDI, IPR-1G-HDMI, IPR-1G-SDI
- AJA IP25-R
- AJA KUMO Routers and Control Panels, FW v4.5.0 and later (with USB port)
- AJA Mini-Connect

Obtaining eMini-Setup

eMini-Setup software for Windows can be obtained directly at this link:

- <https://www.aja.com/products/aja-eminisetup/support>

Manuals for the above products are available via the support sections of their product pages on the AJA website:

- <https://www.aja.com/support>

Firmware Upgrade Procedure

To use eMini-Setup to update firmware for the above products, please refer to the appropriate individual product manual(s) as outlined above. Note that eMini-Setup cannot update firmware on ColorBox.

Fixes, Changes and improvements in eMini-Setup v2.4.4

- This software updates an internal component to improve compatibility with future versions of Windows.

Known Issues

- This software requires Windows 10 version 22H2 or higher. Customers running earlier versions of Windows should remain on v2.4.3
- All KUMO routers and control panels (with USB port) must be updated to KUMO firmware version 4.5.0 or higher before eMini-Setup can see it and be used to configure it.
- Communication between a PC and AJA Mini-Converter may be negatively impacted by certain USB hubs or extender cables. If you experience connectivity issues, try using a different USB hub, directly connecting the AJA Mini-Converter to your PC, and eliminating any passive USB extension cables.
- When user authentication is disabled using eMini-Setup, open login pages will not redirect automatically. On Mini-Connect, click the "Login" button without a password. On KUMO, HELO, HELO Plus, IPT-1G-SDI, IPT-1G-HDMI, IPR-1G-SDI, IPR-1G-HDMI, IPR-10G-HDMI, IPR-10G2-HDMI, and IPR-10G2-SDI, point the browser at the device's IP address and click the "Login" button without a password to log back in. For ColorBox and IP25-R, simply point the browser at the devices IP address.

Technical Support

AJA Technical Support is free and available to help answer questions or resolve issues with any of your AJA products.

To contact AJA Technical Support:

Email: support@aja.com

Phone: +1-530-271-3190

Fax: +1-530-274-9442

Web: <https://www.aja.com/support/contact>

Shipping: 180 Litton Dr. Grass Valley, CA 95945 USA