



3GM

The 3GM is versatile and economical tool for interconnecting dual link 1.5G SMPTE372M and 3G SMPTE425M. 3GM either for dual 1.5G to 3G or 3G to dual 1.5G conversion. Additionally, 3GM's 3G HD-SDI output is configurable for SMPTE425M type A or B. The 3GM can even convert 3G from/to type A or B. 3GM also provides a monitor output which is a single link SMPTE292M 1.5G HD-SDI. The 3GM is also compatible with SMPTE259M 270Mb SDI.

\$495 US MSRP

<https://www.aja.com/products/3gm>

Video Formats

- 3 Gb, 1.5 Gb, 270 Mb Auto Select

• Operating Altitude: <3,000 meters (<10,000 feet)

Video Inputs / Outputs

- 2 HD-SDI, SDI (SMPTE 259/292/296/424), 2 x BNC

Cable Equalization

- (1694 Coax)
- 3 Gb, 120m
- 1.5 Gb, 200m
- 270 Mb, 350m

Input / Output Return Loss

- >15db, 270 Mb - 3 Gb

Size (w x d x h)

- 4.6" x 2.4" x 1.0" (117mm x 61mm x 25mm)

Power

- +5VDC Regulated, 6 Watts, power supply required, included with purchase

Environment

- Safe Operating Temperature: 0 to 40 degrees C (32 to 104 degrees F)
- Safe Storage Temperature (Power OFF): -40 to 60 degrees C (-40 to 140 degrees F)
- Operating Relative Humidity: 10-90% noncondensing