



## DRM2

---

DRM2 is a 3RU rackmount frame to professionally mount, power and hold up to 12 AJA Mini-Converters of any current size/form factor. This rackmount frame will deliver enough power to support any currently available AJA Mini-Converter, with a total power delivery of up to 200 watts.

**\$1295 and \$1495 US**

MSRP

<https://www.aja.com/products/drm2>

---

### User Interface

---

- 12x mounting slots for any AJA Mini-Converters
- Converters may be installed without removing the frame from the rack

### Size (w x d x h)

---

- 19.0" x 15.0" x 5.25" (48.26 x 38.1 x 13.34 cm)

### Weight

---

- DRM2 with 12x carriers, hardware, power harness, and power cord: 9.3 lbs (4.2 kg)
- DRM2 faceplate without fans 0.9 lbs (0.4 kg)
- DRM2 faceplate with fans 2.1 lbs (0.9 kg)

### Power

---

- Universal 100-240V, 50/60Hz power input
- 12x +5V DC regulated outputs (hardwired to power supply)
- Power Consumption: 200 Watts maximum

**Note:** If the ambient temperature is under 30C, an active faceplate is recommended if power consumption exceeds 100W. If the ambient temperature is over 30C, an active faceplate is recommended if power consumption exceeds 75W. Please consult the Tech Specs of your Mini-Converters to calculate expected power consumption.

### Environment

---

- Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <2,500 meters (<8,000 feet)