



# Hi5-Plus

Bring HDMI and 3G-SDI devices together for a full range of monitoring and recording solutions in the edit suite, on set or at live events. Convenient USB setup using AJA MiniConfig on Mac or PC for easy remote configuration.

**\$420 US MSRP**

<https://www.aja.com/products/hi5-plus>

## Video Formats

- (2K) 2K x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (2K) 2K x 1080PsF\* 23.98, 24, 25, 29.97, 30
- (HD) 1080i 50, 59.94, 60
- (HD) 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1080PsF\* 23.98, 24, 25, 29.97, 30
- (HD) 720p 50, 59.94, 60
- (SD) 625i
- (SD) 525i

\*NOTE: converts to progressive

- Safe Operating Temperature: 0 to 40 degrees C (32 to 104 degrees F)
- Safe Storage Temperature (Power OFF): -40 to 60 degrees C (-40 to 140 degrees F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)

## Video Input

- 3G-SDI with embedded audio

## Video Outputs

- HDMI with embedded audio up to 8-Channels (selectable by Mini-Config)
- 8-bit RGB 4:4:4
- 10-bit YCbCr 4:2:2
- 12-bit

## Audio Input

- SDI embedded audio, select from 16-Channels

## Audio Output

- 2-Channel RCA style (-10dBu nominal)

## Size (w x d x h)

- 4.6" x 2.4" x 1.0" (117mm x 61mm x 25mm)

## Power

- Uses AJA power supply model DWP-U-R1, included with purchase
- 100-240V, 50/60 Hz universal input
- +5V DC regulated, 7.5 watt capacity

## Environment