



OG-FIBER-2T-X

The OG-FIBER-2T-X is a state of the art, openGear compatible, 2-channel 3G-SDI to Fiber converter with CWDM SFP options, enabling 3G-SDI signals to be extended up to 10 km (32,808 ft) over standard single-mode fiber optic cable. The two 3G-SDI inputs are completely independent allowing different 3G-SDI rates to be carried on each channel.

\$545 US MSRP

<https://www.aja.com/products/og-fiber-2t-x>

Video Formats

- 100 Mbps - 3 Gbps, format agnostic

degrees F)

- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)

Video Input Digital

- 2-Channel independent 3G-SDI Inputs, SMPTE-259/292/424

Video Output Digital

- 2-Channel independent CWDM LC Fiber Outputs, SMPTE-297*
- Optical Power: -5dBm (min), 0dBm (max)
- Extinction Ratio: 7.5dB (Typ)

**Please see SFP Configurator for CWDM wavelength choices*

Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.966 Gbps, 2.970 Gbps - Auto Select
- All other rates are passed through and not reclocked

Size (w x d x h)

- openGear standard form factor, front slot and rear card
- Two slots required for each card

Power

- openGear frame compatible, 2.5 watts max per card

Environment

- Safe Operating Temperature: 0 to 40 degrees C (32 to 104 degrees F)
- Safe Storage Temperature (Power OFF): -40 to 60 degrees C (-40 to 140