



# OG-FiDO-2T-X

The OG-FiDO-2T-X is a state of the art, openGear compatible, 2-channel 3G-SDI to Fiber converter with CWDM SFP options, enabling 3G-SDI signals to be extended up to 10 km (32,808 ft) over standard single mode fiber optic cable. The two 3G-SDI inputs are completely independent allowing different 3G-SDI rates to be carried on each channel.

**\$1240 US MSRP**

Designed for use in high density openGear 2RU frames including AJA's OG-X-FR frame, new DashBoard software support on Windows®, macOS® and Linux® offers remote control and monitoring of the openGear architecture and provides convenient and industry standard configuration, monitoring and control options over a PC or local network.

<https://www.aja.com/products/og-fido-2t-x>

## Video Formats

- 150 Mbps - 3 Gbps, format agnostic

## Video Input Digital

- 2-Channel independent 3G-SDI Inputs, SMPTE-259/292/424

## Video Output Digital

- 2-Channel independent CWDM LC Fiber Outputs, SMPTE-259/292/424
- Nominal Wavelength:
  - SFP Option 1: 1271 nm & 1291 nm
  - SFP Option 2: 1311 nm & 1331 nm
  - SFP Option 3: 1351 nm & 1371 nm
  - SFP Option 4: 1391 nm & 1411 nm
  - SFP Option 5: 1431 nm & 1451 nm
  - SFP Option 6: 1471 nm & 1491 nm
  - SFP Option 7: 1511 nm & 1531 nm
  - SFP Option 8: 1551 nm & 1571 nm
  - SFP Option 9: 1591 nm & 1611 nm
- Optical Power: -5dBm (min), 0dBm (max)
- Extinction Ratio: 7.5dB (Typ)

**Note:** Please see SFP Configurator for CWDM wavelength choices

## Reclocking

- 270 Mbps, 1.483 Gbps, 1.485 Gbps, 2.966 Gbps, 2.970 Gbps - Auto Select
- All other rates are passed through and not reclocked

## User Interface

- openGear DashBoard network control software via Windows, macOS or Linux

## Size (w x d x h)

- openGear standard form factor, front slot and rear card. Two slots required for each card.

## Weight

- 0.5 lb (0.3 kg)

## Power

- openGear frame compatible, 2.5 watts max per card

## Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)