



## OG-HA5-12G

AJA's OG-HA5-12G converts an HDMI 2.0 input to 12G-SDI for 4K/UltraHD single link outputs. OG-HA5-12G includes two 12G-SDI distribution amplifier outputs with 8 or 2-channels of embedded audio from an HDMI source or two-channel analog audio (RCA) input.

**\$999** US MSRP

OG-HA5-12G also supports Extended Display Identification Data (EDID) emulation, which ensures the connected source continuously supplies custom preferred video formats on output.

OG-HA5-12G-T and OG-HA5-12G-T-ST Fiber SFP-equipped models are single channel transmitters capable of extending HDMI 4K/UltraHD signals over long distances, up to 10km over a single LC or ST Fiber link respectively. These models ship with SFPs installed, and include all functionality of the HA5-12G, with the added benefit of extending audio and video signals further.

<https://www.aja.com/products/og-ha5-12g>

### Video Formats

- (4K) 4096x2160p
- (UltraHD) 3840x2160p
- (2K) 2048x1080p
- (HD) 1920x1080p
- (HD) 1920x1080i
- (HD) 1280x720p
- (SD) 720x576i
- (SD) 720x480i

**Note:** Raster and Frame Rate Dependent, please see OG-12GM Video Formats in the Download / Documents section of the website product page.

### Video Input Digital

- 1x HDMI Type A connector, HDMI v2.0b
  - HDR Infoframe decoder as defined in CTA-861.3 and HDMI v2.0b
  - HDR VPID generation with pass-through or override for Colorimetry and Transfer Characteristic
  - YCbCr 4:2:2/4:4:4/4:2:0
  - RGB 4:4:4, SMPTE or Full level
  - 24, 30, or 36-bits Per Pixel (HFR 4K/UltraHD 4:4:4 limited to 24 BPP)
  - (4K) 4096x2160p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
  - (UltraHD) 3840x2160p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
  - (2K) 2048x1080p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
  - (HD) 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
  - (HD) 1920x1080i 50, 59.94, 60
  - (HD) 1280x720p 50, 59.94, 60
  - (SD) 720x576i 50
  - (SD) 720x480i 59.94

### HDCP Decryption

- Not supported. By definition, SDI outputs are unencrypted.

### Video Output Digital

- 1x 12G-SDI BNC, SMPTE 259/292/424/2081/2082
  - YCbCr 4:2:2/4:4:4
  - RGB 4:4:4, SMPTE or Full level
  - 10-bit, 12-bit\*
- 1x 12G-SDI
  - (4K) 4096x2160p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
  - (UltraHD) 3840x2160p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- 1x 6 Gb SDI
  - (4K) 4096x2160p 23.98, 24, 25, 29.97, 30
  - (UltraHD) 3840x2160p 23.98, 24, 25, 29.97, 30
- 1x 3 Gb SDI (Level A or B Dual Link)
  - (2K) 2048x1080p 23.98, 24, 25, 29.97, 30, 47.95, 48, 50, 59.94, 60
  - (2K) 2048x1080PsF 23.98, 24, 25, 29.97, 30
  - (HD) 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
  - (HD) 1920x1080PsF 23.98, 24, 25, 29.97, 30
  - (HD) 1920x1080i 50, 59.94, 60
  - (HD) 1280x720p\*\* 50, 59.94, 60
- 1x 1.5 Gb SDI
  - (2K) 2048x1080p 23.98, 24, 25, 29.97, 30
  - (2K) 2048x1080PsF 23.98, 24, 25, 29.97, 30
  - (HD) 1920x1080p 23.98, 24, 25, 29.97, 30
  - (HD) 1920x1080PsF 23.98, 24, 25, 29.97, 30
  - (HD) 1920x1080i 50, 59.94, 60
  - (HD) 1280x720p 50, 59.94, 60
- 1x 270 Mb SDI
  - (SD) 625i 50
  - (SD) 525i 59.94

\*Some 12-bit formats not supported, please see OG-HA5-12G Video Formats in Documents and Manual.

\*\*1280x720p is Level A Only

## Video Output Digital - Additional for OG-HA5-12G-T Only

---

- 1x 12G-SDI Fiber LC connector, SMPTE 297/259/292/424/2081/2082
  - Nominal Wavelength: Tx 1260 nm (min), 1310 nm (typ), 1360 nm (max)
  - Optical Power: -5 dBm (min), 0.5 dBm (max)
  - Extinction Ratio: 3.5 dB (min)

## Video Output Digital - Additional for OG-HA5-12G-T-ST Only

---

- 1x 12G-SDI Fiber ST connector, SMPTE 297/259/292/424/2081/2082
  - Nominal Wavelength: Tx 1260 nm (min), 1310 nm (typ), 1360 nm (max)
  - Optical Power: -5 dBm (min), 2 dBm (max)
  - Extinction Ratio: 3.5 dB (min)

## Audio Pass-Through Formats

---

- PCM
- Dolby Digital (AC-3)
- Dolby Digital Plus (E-AC-3), including Atmos Immersive Sound (JOC)

## Audio Input Digital

---

- HDMI embedded audio, 24-bit, 8-channel

## Audio Input Analog

---

- 2x 3-pin terminal block connector, 2-channel balanced analog audio +24dBu (nominal)

## Audio Output Digital

---

- SDI embedded audio, 24-bit (SD limited to 20-bit), 16-channel

## User Interface

---

- openGear DashBoard network control software via Windows, macOS, or Linux

## Size

---

- openGear standard form factor, front slot and rear card
- Two slots required for each card

## Weight

---

- 0.5 lb (0.3 kg)

## Power

---

- openGear frame compatible, 14 watts max per card

## Environment

---

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)