



## ROI-DP

AJA's ROI-DP Mini-Converter allows exceptionally high quality conversion of computer DisplayPort outputs to baseband video over SDI at an affordable price and a very portable size. With extensive audio functionality, incredible image scaling as well as aspect and frame rate conversion, ROI fulfills the growing need to properly incorporate computer signals into the video world without sacrificing budget or space.

**\$1245 US MSRP**

<https://www.aja.com/products/roi-dp>

### Video Input Formats

- Computer Signals:
  - WUXGA (1920 x 1200) 60 Hz max
  - VGA (640 x 480) minimum
- Video Signals:
  - (HD) 1920 x 1080i 50, 59.94
  - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
  - (HD) 1280 x 720p 50, 59.94, 60
  - (SD) 625i, 525i
  - (SD) 580p, 480p

**Note:** Frame rates limited by the 166 mHz max pixel rate of the DP receiver

### Video Output Formats

- (HD) 1920 x 1080p 50, 59.94, 60, SMPTE 425-1 Level A mapping structure 1 (4:2:2 10-bit YCbCr)
- (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30
- (HD) 1920 x 1080i 50, 59.94, 60
- (HD) 1280 x 720p 50, 59.94, 60
- (SD) 625i 25
- (SD) 525i 29.97

### Color Range

- Full
- SMPTE

### Reference Input

- Supported reference video inputs include:
  - 1080i tri-level sync
  - 1080p tri-level sync
  - 720p tri-level sync
  - PAL 625 bi-level sync
  - NTSC 525 bi-level sync

### Video Input

- 1x DisplayPort 1.1a input connector

### Video Outputs

- DisplayPort
  - 1x DisplayPort pass through connector
- SDI
  - 3G-SDI, SMPTE-259/292/424, 1 x BNC

### HDCP

- ROI-DP does not encode the DisplayPort output with HDCP encryption
- ROI-DP does not accept HDCP input

### Audio Inputs

- 1x Analog 3.5mm TRS, 2-channel
- DisplayPort embedded audio, 24-bit, 8-channel

### Audio Outputs

- SDI embedded audio, 24-bit, 2-channel or 8-channel
- DisplayPort embedded audio, 24-bit, 8-channel

### User Interface

- USB port used with supplied cable and Mini-Config software application to configure device via Mac or Windows

### Size (w x d x h)

- 5.77" x 4.02" x 0.9" (146.5 x 102.2 x 22.9 mm)

### Weight

- 0.5 lb (0.3 kg)



## Power

---

- Universal power supply included
- 100-240V, 50/60 Hz Universal Input
- +5 to 20V DC regulated, 7 watts max

## Environment

---

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)