DRM-Rackmount Frame

Mini-Converter related details for use in the DRM and DRM2-Plus

Mini-Converter	Max Power Consumption	Dimensions (W x D x H)	How Many Fit per DRM*	How Many Fit per DRM2-Plus
3G-AM	5 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**10**	**12**
3G-AMA	5 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**10**	**12**
3GDA	3 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**12**	**12**
12G-AM	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AM-R	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AM-R-ST	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AM-T	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AM-T-ST	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AM-TR	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AMA	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AMA-R	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AMA-R-ST	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AMA-T	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AMA-T-ST	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12G-AMA-TR	10 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**5**	**12**
12GDA	3 watts	5.62” x 3.10 x 1.00” (142.7mm x 79mm x 25mm)	**12**	**12**
12GM	12 watts	5.76” x 4.02” x 0.90” (146.31 × 102.11 × 22.86 mm)	**4**	**12**
ADA4	3 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**12**	**12**
C10DA	2 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**12**	**12**
DANTE-12GAM	25 watts	5.00” x 8.09” x 1.65” (127 x 205.49 x 41.81 mm)	**NA**	**6**
FiDO-2R	3 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-2R-12G	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-2R-MM	3 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-2T	3 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-2T-12G	3.5 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-2T-MM	3 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-4R	5 watts	4.60” x 4.02” x 0.85” (117.00 x 102.11 x 21.60 mm)	**10**	**12**
FiDO-4R-MM	5 watts	4.60” x 4.02” x 0.85” (117.00 x 102.11 x 21.60 mm)	**10**	**12**
FiDO-4R-ST	4 watts	5.80” x 3.90” x 0.80” (147.00 x 99.00 x 20.00 mm)	**12**	**12**
FiDO-4T	5 watts	4.60” x 4.02” x 0.85” (117.00 x 102.11 x 21.60 mm)	**10**	**12**
FiDO-4T-MM	5 watts	4.60” x 4.02” x 0.85” (117.00 x 102.11 x 21.60 mm)	**10**	**12**

** Note: Maximum of this particular Mini-Converter, power consumption of all Mini-Converters can not exceed 50 watts in the DRM.*

*** Note: 24 Mini-Converters will fit if combined with the additional purchase of DRM2-Plus Y-Cable, (12 pack bundle of Y-Cable)*

DRM-Rackmount Frame

Mini-Converter related details for use in the DRM and DRM2-Plus

Mini-Converter	Max Power Consumption	Dimensions (W x D x H)	How Many Fit per DRM*	How Many Fit per DRM2-Plus
FiDO-4T-ST	4 watts	5.80” x 3.90” x 0.80” (147.00 x 99.00 x 20.00 mm)	**12**	**12**
FiDO-R	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-R-12G	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-R-12G-ST	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-R-MM	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-R-SC	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-R-ST	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-T	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-T-12G	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-T-12G-ST	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-T-MM	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-T-SC	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-T-ST	2 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-TR	3 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-TR-12G	4 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FiDO-TR-MM	3 watts	4.60” x 1.71” x 0.85” (117.00 x 43.50 x 21.60 mm)	**12**	**24****
FS-Mini	7 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**7**	**12**
GEN10	2 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**12**	**12**
HA5-12G	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**
HA5-12G-T	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**
HA5-12G-T-ST	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**
HA5-4K	10 watts	5.76” x 4.02” x 0.90” (146.31 × 102.11 × 22.86 mm)	**8**	**12**
HA5-Fiber	4.5 watts	4.40” × 2.40” × 1.00” (112.00 × 61.00 × 25.00 mm)	**10**	**24****
HA5-Plus	7.5 watts	4.60” × 2.40” × 1.00” (116.84 × 60.96 × 25.4 mm)	**6**	**24****
HD5DA	2.5 watts	5.80” x 2.40” x 1.00” (131.00 x 61.00 x 25.00 mm)	**12**	**24****
HDP3	6.5 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**7**	**12**
Hi5-12G	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**
Hi5-12G-R	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**
Hi5-12G-R-ST	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**
Hi5-12G-TR	11 watts	4.60” x 4.02” x 0.90” (116.84 x 102.11 x 22.86 mm)	**4**	**12**

** Note: Maximum of this particular Mini-Converter, power consumption of all Mini-Converters can not exceed 50 watts in the DRM.*

*** Note: 24 Mini-Converters will fit if combined with the additional purchase of DRM2-Plus Y-Cable, (12 pack bundle of Y-Cable)*

DRM-Rackmount Frame

Mini-Converter related details for use in the DRM and DRM2-Plus

Mini-Converter	Max Power Consumption	Dimensions (W x D x H)	How Many Fit per DRM*	How Many Fit per DRM2-Plus
Hi5-4K-Plus	12 watts	5.76” x 4.02” x 0.90” (146.31 x 102.11 x 22.86 mm)	**4**	**12**
Hi5-Fiber	3 watts	4.60” x 2.40” x 1.00” (116.84 x 60.96 x 25.40 mm)	**12**	**24****
Hi5-Plus	7.5 watts	4.60” × 2.40” × 1.00” (117.00 × 61.00 × 25.00 mm)	**6**	**24****
IP25-R	25 watts	5.00” x 8.09” x 1.65” (127 x 205.49 x 41.81 mm)	**NA**	**6**
IPT-10G2-HDMI	13 watts	5.00” x 5.75” x 0.88” (127 x 146.05 x 19.05mm)	**3**	**12**
IPT-10G2-SDI	13 watts	5.00” x 5.75” x 0.88” (127 x 146.05 x 19.05mm)	**3**	**12**
ROI-DP	7 watts	5.77” x 4.02” x 0.90” (146.56 x 102.11 x 22.86 mm)	**7**	**12**
ROI-DVI	8 watts	5.77” x 4.02” x 0.90” (146.56 x 102.11 x 22.86 mm)	**6**	**12**
ROI-HDMI	8 watts	5.77” x 4.02” x 0.90” (146.56 x 102.11 x 22.86 mm)	**6**	**12**
ROI-SDI	7 watts	5.77” x 4.02” x 0.90” (146.56 x 102.11 x 22.86 mm)	**7**	**12**
UDC	7 watts	5.80” x 3.10” x 1.00” (147.32 x 78.74 x 25.40 mm)	**7**	**12**
UDC-4K	25 watts	5.00” x 8.09” x 1.65” (127 x 205.49 x 41.81 mm)	**NA**	**6**
V2Analog™	3 watts	5.10” × 2.40” × 1.00” (129.54 × 60.96 × 25.40 mm)	**12**	**24****
V2Digital™	3 watts	5.10” × 2.40” × 1.00” (129.54 × 60.96 × 25.40 mm)	**12**	**24****

** Note: Maximum of this particular Mini-Converter, power consumption of all Mini-Converters can not exceed 50 watts in the DRM.*

*** Note: 24 Mini-Converters will fit if combined with the additional purchase of DRM2-Plus Y-Cable, (12 pack bundle of Y-Cable)*